

Repeater power supply - MACX MCR-SL-RPSSI-2I-SP - 2924838

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Measuring transducer repeater power supply and input signal conditioner, HART-transparent. Transmits supplied or active 0/4 mA ... 20 mA electrically isolated signals from the field to two loads. 4-way electrical isolation, Push-in connection, SIL, PL.

Your advantages

- ✓ Power supply possible via DIN rail connector
- ✓ Up to SIL 2 according to EN 61508
- ✓ Installation in zone 2, protection type "n" (EN 60079-15) permitted
- ✓ Plug-in screw or spring-cage connection technology (Push-in technology), with integrated sockets for HART communicators
- ✓ 0/4 ... 20 mA input (powered or not powered)
- ✓ Two electrically isolated 0/4 mA ... 20 mA (active) outputs
- ✓ 4-way electrical isolation
- ✓ Bidirectional transmission of digital HART communication signals (both outputs)



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 572057
GTIN	4046356572057
Weight per Piece (excluding packing)	160.000 g
Custom tariff number	85437090
Country of origin	Germany