



Main

Device short name	OF SD SDE SDV
Product or component type	Auxiliary contact
Range compatibility	Compact NS630b...1600 Compact NS1600b...3200 Compact INS Compact INSE Compact INSJ Compact INV Compact NG Compact NR Compact NSX EasyPact CVS
Offer type	C5 C4
Signal contacts composition	1 NO/NC

Complementary

Auxiliary contacts type	Standard
Auxiliary contacts operation	Early-make Early-break
Mounting mode	Clip-on
[I _{th}] conventional free air thermal current	6 A
[I _e] rated operational current	AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 220/240 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 380/440 V AC 50/60 Hz AC-12: 6 A at 48 V AC 50/60 Hz AC-12: 6 A at 480 V AC 50/60 Hz AC-12: 6 A at 660/690 V AC 50/60 Hz AC-15: 0.1 A at 660/690 V AC 50/60 Hz

AC-15: 1.5 A at 480 V AC 50/60 Hz
 AC-15: 2 A at 380/440 V AC 50/60 Hz
 AC-15: 4 A at 220/240 V AC 50/60 Hz
 AC-15: 5 A at 110 V AC 50/60 Hz
 AC-15: 6 A at 24 V AC 50/60 Hz
 AC-15: 6 A at 48 V AC 50/60 Hz
 DC-12: 0.3 A at 250 V DC
 DC-12: 0.6 A at 110 V DC
 DC-12: 2.5 A at 48 V DC
 DC-12: 6 A at 24 V DC
 DC-14: 0.03 A at 250 V DC
 DC-14: 0.05 A at 110 V DC
 DC-14: 0.2 A at 48 V DC
 DC-14: 1 A at 24 V DC

Minimum load	100 mA at 24 V
Width	1 cm
Accessory / separate part category	Spare part for Compact NS630b...1600 Spare part for Compact NS1600b...3200

Environment

Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-25...70 °C

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------