

## Coupling relay - PSR-SCP-120UC/URM/5X1/2X2 - 2981402

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Safe coupling relay with force-guided contacts, 5 N/O contacts, 2 N/C contacts, 1-channel, plug-in screw terminal block, width: 22.5 mm

The figure shows a product version of the article

### Your advantages

- ✓ Suitable up to category 1, PL c (EN ISO 13849-1), SIL 1 (EN 62061), SIL 1 (IEC 61508)
- ✓ Safe readback due to force-guided signal contact in accordance with EN 50205
- ✓ Easy proof test according to IEC 61508 thanks to integrated signal contact
- ✓ 1 or 2-channel control
- ✓ 5 enabling current paths, 2 confirmation current paths
- ✓ 120 V version



### Key Commercial Data

|                                      |                                                                                                         |
|--------------------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit                         | 1 pc                                                                                                    |
| GTIN                                 | <br>4 017918 944179 |
| GTIN                                 | 4017918944179                                                                                           |
| Weight per Piece (excluding packing) | 180.000 g                                                                                               |
| Custom tariff number                 | 85364900                                                                                                |
| Country of origin                    | Germany                                                                                                 |