

Coupling relay - PSR-SCP- 24DC/FSP/1X1/1X2 - 2981978

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling relay for SIL 3 high/low demand applications, couples digital output signals to the periphery, 1 enabling current path, 1 signal contact, module for safe state off applications, test pulse filter, fuse, plug-in screw connection, 17.5 mm width

Your advantages

- ✓ Narrow 17.5 mm housing
- ✓ Up to SIL 3 in accordance with IEC 61508
- ✓ With built-in, replaceable fuse in the enabling current path
- ✓ Easy proof test according to IEC 61508 thanks to integrated signal contact
- ✓ Long service life thanks to filtering of controller test pulses
- ✓ Forcibly guided contacts according to EN 50205
- ✓ 1 enabling current path
- ✓ Couples digital output signals from failsafe controllers to I/O devices (valves, etc.) for electrical isolation and power adaptation



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 448352
GTIN	4046356448352
Weight per Piece (excluding packing)	160.000 g
Custom tariff number	85364190
Country of origin	Germany