

Safety module - IB IL 24 PSDO 8-PAC - 2985631

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Safety-related digital output module, IP20 degree of protection, for SafetyBridge, INTERBUS-Safety, and PROFIsafe systems. The module has four safe digital outputs for two-channel assignment or eight safe digital outputs for single-channel assignment

Product Description

The safety module is an output module from the Inline product range designed for use at any point within a SafetyBridge, INTERBUS-Safety or PROFIsafe system. The transmission speed of the safety module can be set to 500 kBaud or 2 Mbaud using a switch. One transmission speed must be used consistently within a station. The module has four safe digital outputs for two-channel assignment or eight digital outputs for single-channel assignment.

Your advantages

- ✓ SIL 3 according to IEC 61508/EN 61508
- ✓ SIL 3 in accordance with EN 62061
- ✓ PL e in accordance with EN ISO 13849-1



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 131605
GTIN	4046356131605
Weight per Piece (excluding packing)	360.000 g
Custom tariff number	85389091
Country of origin	Germany