

PRODUCT-DETAILS

FS401E-C32/0,03

FS401E-C32/0,03



General Information

Extended Product Type	FS401E-C32/0,03
Product ID	2CCL562110E0324
EAN	7612270104598
Catalog Description	FS401E-C32/0,03
Long Description	Pluggable Residual Current Circuit Breaker with overcurrent Protection for the SMISSLINE TP System acc. IEC/EN/DIN EN 61009-1, EN/DIN EN 61009-2-1 Rated breaking capacity Icn 6kA Tripping characteristic C Rated current In 32A Rated sensitivity I Δn 0.03A Rated voltage Ue 240VAC

Ordering

E-Number (Switzerland)	809122837
EAN	7612270104598
Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Dimensions

Product Net Width	91 mm
Product Net Height	91 mm
Product Net Length	72 mm
Product Net Depth / Length	72 mm

Product Net Weight	200 g
--------------------	-------

Container Information

Package Level 1 Units	carton 2 piece
Package Level 1 Width	101 mm
Package Level 1 Height	89 mm
Package Level 1 Depth / Length	76 mm
Package Level 1 Gross Weight	458 g
Package Level 1 EAN	7612270104598

Environmental

Ambient Air Temperature	Operation -25...40 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0.03 A
-------------------------------------	--------

Additional Information

Ambient Temperature	-25...40 °C
Degree of Protection	IP20
Energy Limiting Class	3
Number of Poles	2
Number of Protected Poles	1
Operating Characteristic	Instantaneous
Overvoltage Category	III
Pollution Degree	2
Position of Neutral Terminals	Right
Power Loss	5.53 W
Product Main Type	FS400
Product Name	Residual Current Circuit Breaker with Overcurrent Protection
Rated Service Short-Circuit Breaking Capacity, in % of I _{cu} (I _{CS})	50 %
Rated Cross-Section	1 - Solid-Core 0...35 mm ² 4 - Multi-Wired 0...35 mm ²
Rated Current (I _n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Residual Current	30 mA
Rated Voltage (U _r)	240 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Insulation Voltage (U _i)	500 V
Rated Operational Current (I _e)	32 A
Rated Operational Voltage	240 V AC

Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 6 kA
Rated Short-Circuit Capacity (I_{cn})	(240 V AC) 6 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	6 kA
Release Type	C
RoHS Date	20170426
Standards	IEC 61009-1 EN 61009-1 DIN EN 61009-1 EN 61009-2-1 DIN EN 61009-2-1
Tripping Characteristic	C
Type of Residual Current	A type

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107492A6192
Declaration of Conformity - CE	2CCC451036D0201
Environmental Information	2CCY451206D0201
Instructions and Manuals	9AKK107680A1664
RoHS Information	2CCC413008D0206_RoHS
Dimension Diagram	9AKK107492A6192

Classifications

ETIM 4	EC000003 - Residual current circuit breaker (RCCB)
ETIM 5	EC000003 - Residual current circuit breaker (RCCB)
ETIM 6	EC000905 - Earth leakage circuit breaker
ETIM 7	EC000905 - Earth leakage circuit breaker
Object Classification Code	FB
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Residual Current Circuit Breakers with Overcurrent Protection RCBO

