

## PRODUCT-DETAILS

# S402M-B32

## S402M-B32 Miniature Circuit Breaker



### General Information

|                       |                                                                                                                                                                                                                             |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | S402M-B32                                                                                                                                                                                                                   |
| Product ID            | 2CCS572001R0325                                                                                                                                                                                                             |
| EAN                   | 7612270102051                                                                                                                                                                                                               |
| Catalog Description   | S402M-B32 Miniature Circuit Breaker                                                                                                                                                                                         |
| Long Description      | Pluggable Miniature circuit-breaker for the SMISSLINE TP System acc. IEC/EN 60898-1<br>Rated short-circuit capacity Icn 10 kA Rated current In 32A Tripping characteristic B<br>Poles 2L Rated voltage Ue 230 VAC / 400 VAC |

### Ordering

|                        |               |
|------------------------|---------------|
| E-Number (Switzerland) | 809052807     |
| EAN                    | 7612270102051 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362020      |

### Dimensions

|                            |       |
|----------------------------|-------|
| Product Net Width          | 36 mm |
| Product Net Height         | 91 mm |
| Product Net Length         | 82 mm |
| Product Net Depth / Length | 75 mm |
| Product Net Weight         | 235 g |

## Container Information

|                                |                |
|--------------------------------|----------------|
| Package Level 1 Units          | carton 5 piece |
| Package Level 1 Width          | 100 mm         |
| Package Level 1 Height         | 125 mm         |
| Package Level 1 Depth / Length | 185 mm         |
| Package Level 1 Gross Weight   | 1233 g         |
| Package Level 1 EAN            | 7612270102051  |

## Environmental

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Ambient Air Temperature | Operation -25...55 °C                                           |
| RoHS Status             | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

## Additional Information

|                                                                        |                                |
|------------------------------------------------------------------------|--------------------------------|
| Ambient Temperature                                                    | -25...55 °C                    |
| Connecting Capacity                                                    | Rigid 0 ... 25 mm <sup>2</sup> |
| Degree of Protection                                                   | IP20                           |
| Energy Limiting Class                                                  | 3                              |
| Frequency (f)                                                          | 50 ... 60 Hz                   |
| Number of Poles                                                        | 2                              |
| Number of Protected Poles                                              | 2                              |
| Overvoltage Category                                                   | III                            |
| Pollution Degree                                                       | 3                              |
| Power Loss                                                             | 5.4 W                          |
| Product Main Type                                                      | S400                           |
| Product Name                                                           | Miniature Circuit Breaker      |
| Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cs</sub> | 50 %                           |
| Rated Current (I <sub>n</sub> )                                        | 32 A                           |
| Rated Voltage (U <sub>r</sub> )                                        | 230 / 400 V                    |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )                    | 4 kV                           |
| Rated Insulation Voltage (U <sub>i</sub> )                             | 440 V                          |
| Rated Operational Current (I <sub>e</sub> )                            | 32 A                           |
| Rated Operational Voltage                                              | 240 / 415 V AC                 |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )       | (400 V AC) 7.5 kA              |
| Rated Short-Circuit Capacity (I <sub>cn</sub> )                        | (400 V) 10 kA<br>(230 V) 10 kA |
| Release Type                                                           | B                              |
| RoHS Date                                                              | 20170426                       |
| Standards                                                              | IEC/EN 60898-1                 |
| Tripping Characteristic                                                | B                              |

## Certificates and Declarations (Document Number)

|                       |                 |
|-----------------------|-----------------|
| Data Sheet, Technical | 9AKK107492A6192 |
|-----------------------|-----------------|

|                                |                      |
|--------------------------------|----------------------|
| Information                    |                      |
| Declaration of Conformity - CE | 2CCC451034D0201      |
| Environmental Information      | 2CCY451206D0201      |
| Instructions and Manuals       | 2CCC451019M0109      |
| RoHS Information               | 2CCC413008D0206_RoHS |
| Dimension Diagram              | 9AKK107492A6192      |

**Classifications**

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| ETIM 4                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 5                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 6                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 7                     | EC000042 - Miniature circuit breaker (MCB)                 |
| Object Classification Code | FC                                                         |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

**Categories**

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Miniature Circuit Breakers MCBs

