

## PRODUCT-DETAILS

# S403M-C6

## S403M-C6 Miniature Circuit Breaker



### General Information

|                       |                                                                                                                                                                                                                                                                                      |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | S403M-C6                                                                                                                                                                                                                                                                             |
| Product ID            | 2CCS573001R0064                                                                                                                                                                                                                                                                      |
| EAN                   | 7612270102921                                                                                                                                                                                                                                                                        |
| Catalog Description   | S403M-C6 Miniature Circuit Breaker                                                                                                                                                                                                                                                   |
| Long Description      | Pluggable Miniature circuit-breaker for the SMISSLINE TP System acc. IEC/EN 60898-1; IEC/EN 60947-2 Rated short-circuit capacity Icn 10 kA Rated ultimate short-circuit capacity Icu 25 kA Rated current In 6A Tripping characteristic C Poles 3L Rated voltage Ue 240 VAC / 415 VAC |

### Ordering

|                        |               |
|------------------------|---------------|
| E-Number (Switzerland) | 809176807     |
| EAN                    | 7612270102921 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85362020      |

### Dimensions

|                            |       |
|----------------------------|-------|
| Product Net Width          | 54 mm |
| Product Net Height         | 91 mm |
| Product Net Length         | 82 mm |
| Product Net Depth / Length | 82 mm |
| Product Net Weight         | 401 g |

## Container Information

|                                |                |
|--------------------------------|----------------|
| Package Level 1 Units          | carton 3 piece |
| Package Level 1 Width          | 185 mm         |
| Package Level 1 Height         | 89 mm          |
| Package Level 1 Depth / Length | 101 mm         |
| Package Level 1 Gross Weight   | 1320 g         |
| Package Level 1 EAN            | 7612270102921  |

## Environmental

|                         |                                                                 |
|-------------------------|-----------------------------------------------------------------|
| Ambient Air Temperature | Operation -25...55 °C                                           |
| RoHS Status             | Following EU Directive 2002/95/EC August 18, 2005 and amendment |

## Additional Information

|                                                                                           |                                  |
|-------------------------------------------------------------------------------------------|----------------------------------|
| Ambient Temperature                                                                       | -25...55 °C                      |
| Connecting Capacity                                                                       | Rigid 0 ... 25 mm <sup>2</sup>   |
| Degree of Protection                                                                      | IP20                             |
| Energy Limiting Class                                                                     | 3                                |
| Frequency (f)                                                                             | 50 ... 60 Hz                     |
| Number of Poles                                                                           | 3                                |
| Number of Protected Poles                                                                 | 3                                |
| Overvoltage Category                                                                      | III                              |
| Pollution Degree                                                                          | 3                                |
| Power Loss                                                                                | 5.4 W                            |
| Product Main Type                                                                         | S400                             |
| Product Name                                                                              | Miniature Circuit Breaker        |
| Rated Service Short-Circuit Breaking Capacity, in % of I <sub>cu</sub> (I <sub>cs</sub> ) | 50 %                             |
| Rated Current (I <sub>n</sub> )                                                           | 6 A                              |
| Rated Voltage (U <sub>r</sub> )                                                           | 240 / 415 V                      |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )                                       | 4 kV                             |
| Rated Insulation Voltage (U <sub>i</sub> )                                                | 440 V                            |
| Rated Operational Current (I <sub>e</sub> )                                               | 6 A                              |
| Rated Operational Voltage                                                                 | 240 / 415 V AC                   |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )                          | (400 V AC) 7.5 kA                |
| Rated Short-Circuit Capacity (I <sub>cn</sub> )                                           | (400 V) 10 kA<br>(230 V) 10 kA   |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> )                         | (240 / 415 V AC) 25 kA           |
| Release Type                                                                              | C                                |
| RoHS Date                                                                                 | 20170426                         |
| Standards                                                                                 | IEC/EN 60898-1<br>IEC/EN 60947-2 |
| Tripping Characteristic                                                                   | C                                |

| Certificates and Declarations (Document Number) |                      |
|-------------------------------------------------|----------------------|
| Data Sheet, Technical Information               | 9AKK107492A6192      |
| Declaration of Conformity - CE                  | 2CCC451034D0201      |
| Environmental Information                       | 2CCY451206D0201      |
| Instructions and Manuals                        | 2CCC451019M0109      |
| RoHS Information                                | 2CCC413008D0206_RoHS |
| Dimension Diagram                               | 9AKK107492A6192      |

| Classifications            |                                                            |
|----------------------------|------------------------------------------------------------|
| ETIM 4                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 5                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 6                     | EC000042 - Miniature circuit breaker (MCB)                 |
| ETIM 7                     | EC000042 - Miniature circuit breaker (MCB)                 |
| Object Classification Code | FC                                                         |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

**Categories**

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Miniature Circuit Breakers MCBs

