

PRODUCT-DETAILS

S403M-C16

S403M-C16 Miniature Circuit Breaker



General Information

Extended Product Type	S403M-C16
Product ID	2CCS573001R0164
EAN	7612270102969
Catalog Description	S403M-C16 Miniature Circuit Breaker
Long Description	Pluggable Miniature circuit-breaker for the SMISSLINE TP System acc. IEC/EN 60898-1; IEC/EN 60947-2 Rated short-circuit capacity Icn 10 kA Rated ultimate short-circuit capacity Icu 25 kA Rated current In 16A Tripping characteristic C Poles 3L Rated voltage Ue 240 VAC / 415 VAC

Ordering

E-Number (Switzerland)	809179807
EAN	7612270102969
Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Dimensions

Product Net Width	54 mm
Product Net Height	91 mm
Product Net Length	82 mm
Product Net Depth / Length	82 mm
Product Net Weight	401 g

Container Information

Package Level 1 Units	carton 3 piece
Package Level 1 Width	185 mm
Package Level 1 Height	89 mm
Package Level 1 Depth / Length	101 mm
Package Level 1 Gross Weight	1320 g
Package Level 1 EAN	7612270102969

Environmental

Ambient Air Temperature	Operation -25...55 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information

Ambient Temperature	-25...55 °C
Connecting Capacity	Rigid 0 ... 25 mm ²
Degree of Protection	IP20
Energy Limiting Class	3
Frequency (f)	50 ... 60 Hz
Number of Poles	3
Number of Protected Poles	3
Overvoltage Category	III
Pollution Degree	3
Power Loss	5.7 W
Product Main Type	S400
Product Name	Miniature Circuit Breaker
Rated Service Short-Circuit Breaking Capacity, in % of I _{cs}	50 %
Rated Current (I _n)	16 A
Rated Voltage (U _r)	240 / 415 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Insulation Voltage (U _i)	440 V
Rated Operational Current (I _e)	16 A
Rated Operational Voltage	240 / 415 V AC
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(400 V AC) 7.5 kA
Rated Short-Circuit Capacity (I _{cn})	(400 V) 10 kA (230 V) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(240 / 415 V AC) 25 kA
Release Type	C
RoHS Date	20170426
Standards	IEC/EN 60898-1 IEC/EN 60947-2
Tripping Characteristic	C

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	9AKK107492A6192
Declaration of Conformity - CE	2CCC451034D0201
Environmental Information	2CCY451206D0201
Instructions and Manuals	2CCC451019M0109
RoHS Information	2CCC413008D0206_RoHS
Dimension Diagram	9AKK107492A6192

Classifications	
ETIM 4	EC000042 - Miniature circuit breaker (MCB)
ETIM 5	EC000042 - Miniature circuit breaker (MCB)
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
Object Classification Code	FC
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Plug-in Distribution Systems → Miniature Circuit Breakers MCBs

