

PRODUCT-DETAILS

S804S-UCB63-R

S804S-UCB63-R High Performance MCB



General Information

Extended Product Type	S804S-UCB63-R
Product ID	2CCS864002R1635
EAN	7612271208622
Catalog Description	S804S-UCB63-R High Performance MCB
Long Description	S804S-UCB63-R 4 Poles UCB Characteristic 63A 50kA 750VDC Ringlug

Technical

Standards	IEC/EN 60947-2
Number of Poles	4
Number of Protected Poles	4
Tripping Characteristic	UC-B
Rated Current (I_n)	63 A
Rated Operational Voltage	750 V DC
Rated Voltage (U_r)	750 V
Power Loss	24.8 W at Rated Operating Conditions per Pole 6.2 W
Rated Insulation Voltage (U_i)	1500 V DC
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(750 V DC) 50 kA
Rated Service Short-	(750 V DC) 50 kA

Circuit Breaking Capacity (I _{cs})	
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage (U _{imp})	8 kV
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 50 mm ² Flexible 0 ... 70 mm ²
Built-In Depth (t ₂)	82.5 mm

Environmental

Ambient Air Temperature	Operation -25...60 °C
Environmental Conditions	Damp Heat Cyclic acc. to IEC 60068-2-30 405 + 12 cycle Damp Heat Cyclic acc. to IEC 60068-2-30 55°C @ 90-96 % Damp Heat Cyclic acc. to IEC 60068-2-30 25°C @ 90-100 % Dry Heat Test B acc. to IEC 60068-2-2 16 hours @ 55 °C Dry Heat Test B acc. to IEC 60068-2-2 2 hours @ 70 °C
RoHS Status	Following EU Directive 2011/65/EU

Dimensions

Product Net Width	108 mm
Product Net Depth / Length	82.5 mm
Product Net Height	142 mm
Product Net Weight	980 g

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	152 mm
Package Level 1 Depth / Length	111 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	1030 g
Package Level 1 EAN	7612271208622

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413016D0601
Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413016M0008

RoHS Information	2CCC413016D0601 9AKK107680A3903
------------------	------------------------------------

Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413016M0008
Dimension Diagram	2CCC413003C0201

Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

