

PRODUCT-DETAILS

S804U-K25

S804U-K25 High Performance MCB



General Information

Extended Product Type	S804U-K25
Product ID	2CCS864017R0517
EAN	7612271214159
Catalog Description	S804U-K25 High Performance MCB
Long Description	S804U-K25 4 Pole K Characteristic 25A 50kA 240/415VAC High Performance Circuit Breaker HPCB

Technical

Standards	IEC/EN 60947-2 UL 489
Number of Poles	4
Number of Protected Poles	4
Tripping Characteristic	K
Rated Current (I_n)	25 A
Rated Operational Voltage	240 V AC
Rated Voltage (U_r)	240 / 415 V AC
Power Loss	4.2 W at Rated Operating Conditions per Pole
Rated Insulation Voltage (U_i)	690 V
Rated Short-Circuit Capacity (I_{cn})	(400 V) 40 kA (230 V) 40 kA

Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(415 V AC) 50 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(415 V AC) 40 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Actuator Marking	I / O
Contact Position Indication	ON / OFF / TRIP
Degree of Protection	IP20
Connecting Capacity	Rigid 0 ... 50 mm ² Flexible 0 ... 70 mm ²
Built-In Depth (t_2)	82.5 mm

Environmental

Ambient Air Temperature	Operation -25...60 °C
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Interrupting Rating acc. to UL489	(240 V AC) 50 kA
-----------------------------------	------------------

Dimensions

Product Net Width	106 mm
Product Net Depth / Length	82.5 mm
Product Net Height	95 mm
Product Net Weight	980 g

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	105 mm
Package Level 1 Depth / Length	111 mm
Package Level 1 Height	99 mm
Package Level 1 Gross Weight	1010 g
Package Level 1 EAN	7612271214159

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362020

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CCC413009D0201
Environmental Information	2CCY413207D0203
Instructions and Manuals	2CCC413015M0403
RoHS Information	2CCC413009D0201 9AKK107680A3903

Popular Downloads

Data Sheet, Technical Information	2CCC413003C0208
Instructions and Manuals	2CCC413015M0403
Dimension Diagram	2CCC413003C0201

Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

