

PRODUCT-DETAILS

## E203/45R

## Isolator E203/45r



General Information	
Extended Product Type	E203/45R
Product ID	2CDE283001R0045
EAN	4016779646062
Catalog Description	Isolator E203/45r
Long Description	These devices are suitable for commanding loads and they are realized according EN 60947-3 and EN 60669-1 respectively. Fast removal without dismantling of the busbar. Captive screws with recessed/slotted head. Pozidrive size 2. Add-on of up to 3 auxiliary contact S2C-H6R possible Integrated lay-on edge for labeling system ILS. Locking

Technical	
Standards	IEC/EN 60947-3
Rated Operational Voltage	230 / 400 V AC
Power Loss	2.65 W at Rated Operating Conditions per Pole 0.9 W

Environmental	
RoHS Status	Following EU Directive 2011/65/EU

## **Dimensions**

Product Net Width	52.5 mm
Product Net Height	85 mm
Product Net Depth / Length	69 mm
Product Net Weight	0.29 kg

Container Information	
Package Level 1 Units	3 piece
Package Level 1 Width	92 mm
Package Level 1 Height	80 mm
Package Level 1 Depth / Length	183 mm
Package Level 1 Gross Weight	0.915 kg
Package Level 1 EAN	4016779669009
Package Level 2 Units	36 piece
Package Level 2 Width	275 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	11.38 kg
Package Level 2 EAN	4016779865647

1 piece
85365080

Certificates and Declarations (Document Number)	
Declaration of	2CDK441011D0403
Conformity - CE	
Instructions and	2CSC400002D0208
Manuals	
RoHS Information	2CDK440002K0201

Popular Downloads	
Data Sheet, Technical Information	2CSC400002D0209
Instructions and Manuals	2CSC400002D0208

Classifications	
ETIM 4	EC000216 - Switch disconnector
ETIM 5	EC001545 - Main switch for distribution board
ETIM 6	EC001545 - Main switch for distribution board
ETIM 7	EC001545 - Main switch for distribution board
Object Classification Code	Q
eClass	V11.0 : 27142301

E203/45R 3

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Modular\ DIN\ Rail\ Products \rightarrow Modular\ DIN\ Rail\ Components\ MDRCs \rightarrow Command\ Devices$ 

