

PRODUCT-DETAILS

E203/25G

Isolator E203/25g



General Information

Extended Product Type	E203/25G
Product ID	2CDE283001R1025
EAN	4016779645997
Catalog Description	Isolator E203/25g
Long Description	These devices are suitable for commanding loads and they are realized according EN 60947-3 and EN 60669-1 respectively. Fast removal without dismantling of the busbar. Captive screws with recessed/slotted head. Pozidrive size 2. Add-on of up to 3 auxiliary contact S2C-H6R possible Integrated lay-on edge for labeling system ILS. Locking device as accessories for unauthorized ON/OFF. Approval: VDE, CCC, KEMA

Technical

Standards	IEC/EN 60947-3
Power Loss	0.9 W at Rated Operating Conditions per Pole 0.3 W

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Dimensions

Product Net Width	52.5 mm
Product Net Height	85 mm

Product Net Depth / Length	69 mm
Product Net Weight	0.29 kg

Container Information

Package Level 1 Units	3 piece
Package Level 1 Width	92 mm
Package Level 1 Height	80 mm
Package Level 1 Depth / Length	183 mm
Package Level 1 Gross Weight	0.915 kg
Package Level 1 EAN	4016779669054
Package Level 2 Units	36 piece
Package Level 2 Width	275 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	11.38 kg
Package Level 2 EAN	4016779865395

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CDK441011D0403
Instructions and Manuals	2CSC400002D0208
RoHS Information	2CDK440002K0201

Popular Downloads

Data Sheet, Technical Information	2CSC400002D0209
Instructions and Manuals	2CSC400002D0208

Classifications

ETIM 4	EC000216 - Switch disconnecter
ETIM 5	EC001545 - Main switch for distribution board
ETIM 6	EC001545 - Main switch for distribution board
ETIM 7	EC001545 - Main switch for distribution board
eClass	V11.0 : 27142301

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Modular DIN Rail Components MDRCs → Command Devices

