

PRODUCT-DETAILS

SZ201-B25

Miniature Circuit Breakers MCBs - SZ200 - 1P - B - 25 ampere



General Information

| | |
|-----------------------|--------------------------------------------------------------|
| Extended Product Type | SZ201-B25 |
| Product ID | 2CDS251025R0255 |
| EAN | 4016779996242 |
| Catalog Description | Miniature Circuit Breakers MCBs - SZ200 - 1P - B - 25 ampere |
| Long Description | SZ201-B25 Miniature Circuit Breaker B-Char., 6kA, 25A, 1P |

Technical

| | |
|------------------------------------|-------------------------------------------------------------|
| Number of Poles | 1 |
| Number of Protected Poles | 1 |
| Tripping Characteristic | B |
| Rated Current (I_n) | 25 A |
| Rated Operational Voltage | acc. to IEC 60898-1 230 / 400 V AC |
| Power Loss | at Rated Operating Conditions per Pole 3.2 W |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 440 V Phase to Phase 440 V |
| Operational Voltage | Maximum (Incl. Tolerance) 253 / 440 V AC Minimum 12 V AC |
| Rated Frequency (f) | 50 Hz 60 Hz |
| Energy Limiting Class | 3 |
| Overvoltage Category | III |
| Pollution Degree | 2 |

| | |
|-----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV (6.2 kV @ sea level) (5.0 kV @ 2000 m) |
| Dielectric Test Voltage | 50/60 Hz, 1 min: 2 kV |
| Housing Material | Insulation Group I, RAL 7035 |
| Actuator Type | Toggle |
| Actuator Material | Insulation Group II, Black, Sealable |
| Actuator Marking | I / O |
| Contact Position Indication | ON / OFF |
| Degree of Protection | IP20 |
| Remarks | IP40 in enclosure with cover |
| Electrical Endurance | 20000 AC cycle 20000 cycle |
| Terminal Type | Screw Terminals |
| Screw Terminal Type | Failsafe Bi-directional Cylinder-lift Terminal |
| Connecting Capacity | Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ² |
| Tightening Torque | 2.8 N·m |
| Recommended Screw Driver | Pozidriv 2 |
| Mounting on DIN Rail | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | Any |
| Built-In Depth (t_2) | 69 mm |
| Installation Size | acc. to DIN 43880 1 |
| Power Supply Connection | Arbitrary |
| Suitable for Isolation | Yes |

Environmental

| | |
|------------------------------------------------|-----------------------------------------------------------|
| Ambient Air Temperature | Operation -25 ... +55 °C Storage -40 ... +70 °C |
| Reference Ambient Air Temperature | 30 °C |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g / 2 shocks / 13 ms |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In |
| Environmental Conditions | 28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 % |
| RoHS Status | Following EU Directive 2011/65/EU |

Dimensions

| | |
|----------------------------|----------|
| Product Net Width | 17.5 mm |
| Product Net Depth / Length | 69 mm |
| Product Net Height | 85 mm |
| Product Net Weight | 0.115 kg |

Container Information

| | |
|-----------------------|-----------------|
| Package Level 1 Units | carton 10 piece |
| Package Level 1 Width | 92 mm |

| | |
|--------------------------------|---------------|
| Package Level 1 Depth / Length | 183 mm |
| Package Level 1 Height | 80 mm |
| Package Level 1 Gross Weight | 1.2 kg |
| Package Level 1 EAN | 4016779996600 |
| Package Level 2 Units | 120 piece |
| Package Level 2 Width | 275 mm |
| Package Level 2 Depth / Length | 395 mm |
| Package Level 2 Height | 210 mm |
| Package Level 2 Gross Weight | 14.8 kg |
| Package Level 2 EAN | 4016779996808 |

Ordering

| | |
|------------------------|----------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362010 |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 9AKK107492A7641 |
| Instructions and Manuals | 2CDS207104P0001 |
| RoHS Information | 9AKK107492A7656 |

Popular Downloads

| | |
|--------------------------|-----------------|
| Instructions and Manuals | 2CDS207104P0001 |
|--------------------------|-----------------|

Classifications

| | |
|--------|--------------------------------------------|
| ETIM 6 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 7 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 8 | EC000042 - Miniature circuit breaker (MCB) |
| eClass | V11.0 : 27141901 |
| UNSPSC | 39121614 |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

