

PRODUCT-DETAILS

MCB S203-B3

Miniature Circuit Breaker - S200 - 3P - B - 3 ampere



General Information

Extended Product Type	MCB S203-B3
Product ID	2CDS253001R0035
EAN	4016779926478
Catalog Description	Miniature Circuit Breaker - S200 - 3P - B - 3 ampere
Long Description	Miniature Circuit Breaker MCB S203-B3

Technical

Standards	IEC/EN 60898-1
Number of Poles	3
Number of Protected Poles	3
Tripping Characteristic	B
Rated Current (I_n)	3 A
Rated Operational Voltage	400 V AC
Rated Voltage (U_r)	400 V
Rated Insulation Voltage (U_i)	440 V
Rated Short-Circuit Capacity (I_{cn})	(400 V) 6 kA (230 V) 6 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	2
Rated Impulse	4 kV

Withstand Voltage (U_{imp})

Degree of Protection	IP20
Connecting Capacity	Flexible 0 ... 25 mm ² Rigid 0 ... 35 mm ²
Built-In Depth (t ₂)	69 mm

Environmental

Ambient Air Temperature	Operation -25...55 °C
-------------------------	-----------------------

Dimensions

Product Net Width	0.053 m
Product Net Depth / Length	0.044 m
Product Net Height	0.088 m
Product Net Weight	0.375 kg

Container Information

Package Level 1 EAN	4016779926478
---------------------	---------------

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CDK403001D0605
Environmental Information	2CDK400030D0201
Instructions and Manuals	Printed on packaging
RoHS Information	2CDK400003K0203

Popular Downloads

Data Sheet, Technical Information	9AKK107046A0423
Instructions and Manuals	Printed on packaging

Classifications

ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

