

## PRODUCT-DETAILS

# S201MT-Z4

## Miniature Circuit Breaker - S200MT - 1P - Z - 4 ampere



### General Information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | S201MT-Z4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Product ID            | 2CDS271006R0338                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| EAN                   | 4016779765664                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Catalog Description   | Miniature Circuit Breaker - S200MT - 1P - Z - 4 ampere                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Long Description      | <p>S200MT miniature circuit breakers are designed especially for traction and railway applications. Acc. NF F 16-101/102 the product range S200MT is classified with Exigence 3, enabling the use in all parts of the vehicle. They are current limiting and have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 10 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200MT comply with IEC/EN 60898-1 and IEC/EN 609 47-2. All system pro M compact accessories can be used. Including the bottom-fitting auxiliary contact S2C-Hxx providing the possibility of 50% space saving and the creation of group signals.</p> |

### Technical

|                                 |                              |
|---------------------------------|------------------------------|
| Standards                       | IEC/EN 60947-2               |
| Number of Poles                 | 1                            |
| Number of Protected Poles       | 1                            |
| Tripping Characteristic         | Z                            |
| Rated Current (I <sub>n</sub> ) | 4 A                          |
| Rated Operational Voltage       | acc. to IEC 60947-2 230 V AC |
| Power Loss                      | 2.6 W                        |

at Rated Operating Conditions per Pole 2.6 W

|                                                                   |                                                                                                                                                                                                          |
|-------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rated Insulation Voltage (U <sub>i</sub> )                        | acc. to IEC/EN 60664-1 440 V                                                                                                                                                                             |
| Rated Frequency (f)                                               | 50 Hz<br>60 Hz                                                                                                                                                                                           |
| Rated Ultimate Short-Circuit Breaking Capacity (I <sub>cu</sub> ) | (230 V AC) 15 kA                                                                                                                                                                                         |
| Rated Service Short-Circuit Breaking Capacity (I <sub>cs</sub> )  | (230 V AC) 11.3 kA                                                                                                                                                                                       |
| Overvoltage Category                                              | III                                                                                                                                                                                                      |
| Pollution Degree                                                  | 3                                                                                                                                                                                                        |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> )               | (5.0 kV @ 2000 m)<br>(6.2 kV @ sea level)<br>4 kV                                                                                                                                                        |
| Housing Material                                                  | Insulation Group I, RAL 7035                                                                                                                                                                             |
| Actuator Material                                                 | Insulation Group II, Black, Sealable                                                                                                                                                                     |
| Actuator Marking                                                  | I / O                                                                                                                                                                                                    |
| Degree of Protection                                              | IP20                                                                                                                                                                                                     |
| Remarks                                                           | IP40 in enclosure with cover<br>20000 cycle                                                                                                                                                              |
| Terminal Type                                                     | Screw Terminals                                                                                                                                                                                          |
| Screw Terminal Type                                               | Failsafe Bi-directional Cylinder-lift Terminal                                                                                                                                                           |
| Connecting Capacity                                               | Busbar 10 / 10 mm <sup>2</sup><br>Flexible with Ferrule 0.75 ... 16 mm <sup>2</sup><br>Flexible 0.75 ... 16 mm <sup>2</sup><br>Rigid 0.75 ... 25 mm <sup>2</sup><br>Stranded 0.75 ... 25 mm <sup>2</sup> |
| Tightening Torque                                                 | 2.8 N·m                                                                                                                                                                                                  |
| Recommended Screw Driver                                          | Pozidriv 2                                                                                                                                                                                               |
| Mounting on DIN Rail                                              | TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715<br>TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715                                                                                           |
| Mounting Position                                                 | Any                                                                                                                                                                                                      |
| Built-In Depth (t <sub>2</sub> )                                  | 69 mm                                                                                                                                                                                                    |
| Installation Size                                                 | acc. to DIN 43880 1                                                                                                                                                                                      |
| Power Supply Connection                                           | Arbitrary                                                                                                                                                                                                |

## Environmental

|                                                |                                                           |
|------------------------------------------------|-----------------------------------------------------------|
| Ambient Air Temperature                        | Operation -25 ... +55 °C<br>Storage -40 ... +70 °C        |
| Resistance to Shock acc. to IEC 60068-2-27     | 30g / 3 shocks / 11 ms                                    |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In      |
| Environmental Conditions                       | 28 cycles<br>with 55 °C / 90-96 %<br>and 25 °C / 95-100 % |
| RoHS Status                                    | Following EU Directive 2011/65/EU                         |

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 17.5 mm  |
| Product Net Depth / Length | 69 mm    |
| Product Net Height         | 88 mm    |
| Product Net Weight         | 0.125 kg |

---

**Container Information**

---

|                                |                 |
|--------------------------------|-----------------|
| Package Level 1 Units          | carton 10 piece |
| Package Level 1 Width          | 92 mm           |
| Package Level 1 Depth / Length | 183 mm          |
| Package Level 1 Height         | 80 mm           |
| Package Level 1 Gross Weight   | 1.3 kg          |
| Package Level 1 EAN            | 4016779827089   |

---

---

**Ordering**

---

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85362010 |

---

---

**Certificates and Declarations (Document Number)**

---

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CDK400594D2704 |
| Environmental Information      | 9AKK107680A6947 |
| Instructions and Manuals       | 2CDS207104P0001 |
| RoHS Information               | 2cdk400594d2703 |

---

---

**Popular Downloads**

---

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CDC002053D0204 |
| Instructions and Manuals          | 2CDS207104P0001 |

---

---

**Classifications**

---

|                            |                                            |
|----------------------------|--------------------------------------------|
| Object Classification Code | F                                          |
| ETIM 6                     | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 7                     | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 8                     | EC000042 - Miniature circuit breaker (MCB) |
| eClass                     | V11.0 : 27141901                           |
| UNSPSC                     | 39121614                                   |

---

---

**Accessories**

---

| Identifier      | Description                                                  | Type          | Quantity | Unit Of Measure |
|-----------------|--------------------------------------------------------------|---------------|----------|-----------------|
| 2CDS200922R0001 | S2C-S/H6R - S2C - S/H 6R- 1NA+1NC (1/2 mod.)                 | S2C-S/H6R     | 1        | piece           |
| 2CDS200912R0001 | S2C-H6R - S2C - H 6R- 1NA+1NC (1/2 mod.)                     | S2C-H6R       | 1        | piece           |
| 2CDS200936R0001 | S2C-H11L - S2C-H11L- 1NA+1NC montaggio a sinistra (1/2 mod.) | S2C-H11L      | 1        | piece           |
| 2CDS200936R0002 | S2C-H20L - S2C-H20L- 2NA montaggio a sinistra (1/2 mod.)     | S2C-H20L      | 1        | piece           |
| 2CDS200936R0003 | S2C-H02L - S2C-H02L- 2NC montaggio a sinistra (1/2 mod.)     | S2C-H02L      | 1        | piece           |
| 2CDS200946R0001 | S2C-H6-11R - Auxiliary Contact                               | S2C-H6-11R    | 1        | piece           |
| 2CDS200946R0002 | S2C-H6-20R - Auxiliary Contact                               | S2C-H6-20R    | 1        | piece           |
| 2CDS200946R0003 | S2C-H6-02R - Auxiliary Contact                               | S2C-H6-02R    | 1        | piece           |
| 2CDS200909R0001 | S2C-A1 - S2C - A1- 12-60V c.a./c.c. (1 mod.)                 | S2C-A1        | 1        | piece           |
| 2CDS200909R0002 | S2C-A2 - S2C - A2- 110-415V c.a./110-250 V c.c. (1 mod.)     | S2C-A2        | 1        | piece           |
| 2CSS200911R0001 | S2C-UA 12 DC - S2C - UA 12 DC- 12V c.c. (1 mod.)             | S2C-UA 12 DC  | 1        | piece           |
| 2CSS200911R0002 | S2C-UA 24 AC - S2C - UA 24 AC- 24V c.a. (1 mod.)             | S2C-UA 24 AC  | 1        | piece           |
| 2CSS200911R0003 | S2C-UA 48 AC - S2C - UA 48 AC- 48V c.a. (1 mod.)             | S2C-UA 48 AC  | 1        | piece           |
| 2CSS200911R0004 | S2C-UA 110 AC - S2C - UA 110 AC- 110V c.a. (1 mod.)          | S2C-UA 110 AC | 1        | piece           |
| 2CSS200911R0005 | S2C-UA 230 AC - S2C - UA 230 AC- 230V c.a. (1 mod.)          | S2C-UA 230 AC | 1        | piece           |
| 2CSS200911R0006 | S2C-UA 400 AC - S2C - UA 400 AC- 400V c.a. (1 mod.)          | S2C-UA 400 AC | 1        | piece           |
| 2CSS200911R0007 | S2C-UA 24 DC - S2C - UA 24 DC- 24V c.c. (1 mod.)             | S2C-UA 24 DC  | 1        | piece           |
| 2CSS200911R0008 | S2C-UA 48 DC - S2C - UA 48 DC- 48V c.c. (1 mod.)             | S2C-UA 48 DC  | 1        | piece           |
| 2CSS200911R0009 | S2C-UA 110 DC - S2C - UA 110 DC- 110V c.c. (1 mod.)          | S2C-UA 110 DC | 1        | piece           |
| 2CSS200911R0010 | S2C-UA 230 DC - S2C - UA 230 DC- 230V c.c. (1 mod.)          | S2C-UA 230 DC | 1        | piece           |
| 2CSS201997R0013 | S2C-CM1 - S2C-CM1- S200 1P                                   | S2C-CM1       | 1        | piece           |
| 2CSS203997R0013 | S2C-CM2/3 - S2C-CM2/3-S200 2P-3P                             | S2C-CM2/3     | 1        | piece           |
| 2CSS204997R0013 | S2C-CM4 - S2C-CM4- S200 4P                                   | S2C-CM4       | 1        | piece           |
| GHS2001901R0003 | S2C-DH - S2C-DH                                              | S2C-DH        | 1        | piece           |
| 2CSS200998R0001 | S2C-BP - Mechanical tripping device                          | S2C-BP        | 1        | piece           |
| 2CSS200999R0001 | S2C-EST - S2C-EST                                            | S2C-EST       | 1        | piece           |
| 2CDS200918R0001 | S2C-NT - Hand Operated Neutral                               | S2C-NT        | 1        | piece           |
| 2CCA880100R0001 | sistema misura multipartenze CMS                             | CMS-100PS     | 1        | piece           |
| 2CCA880101R0001 | sistema misura multipartenze CMS                             | CMS-101PS     | 1        | piece           |
| 2CCA880102R0001 | sistema misura multipartenze CMS                             | CMS-102PS     | 1        | piece           |

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

