

PRODUCT-DETAILS

## S204MT-B32

# Miniature Circuit Breaker - S200MT - 4P - B - 32 ampere



### General Information

Extended Product Type	S204MT-B32
Product ID	2CDS274006R0325
EAN	4016779871785
Catalog Description	Miniature Circuit Breaker - S200MT - 4P - B - 32 ampere
Long Description	S204MT-B32 MiniatureCircuitBreaker B-Char.,10kA,32A,4P

### Technical

Standards	IEC/EN 60898-1 IEC/EN 60947-2
Number of Poles	4
Number of Protected Poles	4
Tripping Characteristic	B
Rated Current (I <sub>n</sub> )	32 A
Rated Operational Voltage	acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 400 V AC
Power Loss	16.8 W at Rated Operating Conditions per Pole 4.2 W
Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC/EN 60664-1 440 V
Operational Voltage	Maximum (Incl. Tolerance) 440 V AC Maximum 440 V AC Minimum 12 V AC Minimum 12 V DC
Rated Frequency (f)	50 Hz

	60 Hz
Rated Short-Circuit Capacity ( $I_{cn}$ )	(400 V AC) 10 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(400 V AC) 15 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(400 V AC) 11.3 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	3
Rated Impulse Withstand Voltage ( $U_{imp}$ )	4 kV (6.2 kV @ sea level) (5.0 kV @ 2000 m)
Dielectric Test Voltage	50/60 Hz, 1 min: 2 kV
Housing Material	Insulation Group I, RAL 7035
Actuator Material	Insulation Group II, Black, Sealable
Actuator Marking	I / O
Degree of Protection	IP20
Remarks	IP40 in enclosure with cover
Electrical Endurance	10000 AC cycle 20000 cycle
Terminal Type	Screw Terminals
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Connecting Capacity	Busbar 10 / 10 mm <sup>2</sup> Flexible with Ferrule 0.75 ... 16 mm <sup>2</sup> Flexible 0.75 ... 16 mm <sup>2</sup> Rigid 0.75 ... 25 mm <sup>2</sup> Stranded 0.75 ... 25 mm <sup>2</sup>
Tightening Torque	2.8 N·m
Recommended Screw Driver	Pozidriv 2
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting Position	Any
Built-In Depth ( $t_2$ )	69 mm
Installation Size	acc. to DIN 43880 1
Power Supply Connection	Arbitrary

## Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Reference Ambient Air Temperature	30 °C
Resistance to Shock acc. to IEC 60068-2-27	30g / 3 shocks / 11 ms
Resistance to Vibrations acc. to IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
RoHS Status	Following EU Directive 2011/65/EU

## Dimensions

Product Net Width	70 mm
Product Net Depth / Length	69 mm

Product Net Height	88 mm
Product Net Weight	0.5 kg

### Container Information

Package Level 1 Units	carton 1 piece
Package Level 1 Width	92 mm
Package Level 1 Depth / Length	78 mm
Package Level 1 Height	80 mm
Package Level 1 Gross Weight	0.53 kg
Package Level 1 EAN	4016779866927

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010

### Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CDK400594D2704
Environmental Information	9AKK107680A6947
Instructions and Manuals	2CDS207104P0001
RoHS Information	2cdk400594d2703

### Popular Downloads

Data Sheet, Technical Information	2CDC002053D0204
Instructions and Manuals	2CDS207104P0001

### Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
eClass	V11.0 : 27141901
UNSPSC	39121614

### Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	S2C-S/H6R - S2C - S/H 6R- 1NA+1NC (1/2 mod.)	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R - S2C - H 6R- 1NA+1NC (1/2 mod.)	S2C-H6R	1	piece
2CDS200936R0001	S2C-H11L - S2C-H11L- 1NA+1NC montaggio a sinistra (1/2 mod.)	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L - S2C-H20L- 2NA montaggio a sinistra (1/2 mod.)	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L - S2C-H02L- 2NC montaggio a sinistra (1/2 mod.)	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R - Auxiliary Contact	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R - Auxiliary Contact	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R - Auxiliary Contact	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 - S2C - A1- 12-60V c.a./c.c. (1 mod.)	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 - S2C - A2- 110-415V c.a./110-250 V c.c. (1 mod.)	S2C-A2	1	piece
2CSS200911R0001	S2C-UA 12 DC - S2C - UA 12 DC- 12V c.c. (1 mod.)	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC - S2C - UA 24 AC- 24V c.a. (1 mod.)	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC - S2C - UA 48 AC- 48V c.a. (1 mod.)	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC - S2C - UA 110 AC- 110V c.a. (1 mod.)	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC - S2C - UA 230 AC- 230V c.a. (1 mod.)	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC - S2C - UA 400 AC- 400V c.a. (1 mod.)	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC - S2C - UA 24 DC- 24V c.c. (1 mod.)	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC - S2C - UA 48 DC- 48V c.c. (1 mod.)	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC - S2C - UA 110 DC- 110V c.c. (1 mod.)	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC - S2C - UA 230 DC- 230V c.c. (1 mod.)	S2C-UA 230 DC	1	piece
2CSS201997R0013	S2C-CM1 - S2C-CM1- S200 1P	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 - S2C-CM2/3-S200 2P-3P	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 - S2C-CM4- S200 4P	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH - S2C-DH	S2C-DH	1	piece
2CSS200998R0001	S2C-BP - Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST - S2C-EST	S2C-EST	1	piece
2CDS200918R0001	S2C-NT - Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	sistema misura multipartenze CMS	CMS-100PS	1	piece
2CCA880101R0001	sistema misura multipartenze CMS	CMS-101PS	1	piece
2CCA880102R0001	sistema misura multipartenze CMS	CMS-102PS	1	piece

## Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

