

PRODUCT-DETAILS

S202P-B25

Miniature Circuit Breaker - S200P - 2P - B - 25 ampere



General Information

Extended Product Type	S202P-B25
Product ID	2CDS282001R0255
EAN	4016779589727
Catalog Description	Miniature Circuit Breaker - S200P - 2P - B - 25 ampere
Long Description	System pro M compact S200P miniature circuit breakers are current limiting. They have two different tripping mechanisms, the delayed thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. They are available in different characteristics (B,C,D,K,Z), configurations (1P,1P+N,2P,3P,3P+N,4P), breaking capacities (up to 25 kA at 230/400 V AC) and rated currents (up to 63A). All MCBs of the product range S200P comply with IEC/EN 60898-1, IEC/EN 609 47-2, UL1077 and CSA 22.2 No. 235, allowing the use for residential, commercial and industrial applications. Bottom-fitting auxiliary contact can be mounted on S200P to save 50% space.

Technical

Standards	CSA 22.2 No. 235 IEC/EN 60898-1 IEC/EN 60947-2 UL 1077
Number of Poles	2
Number of Protected Poles	2
Tripping Characteristic	B
Rated Current (I_n)	25 A
Rated Operational Voltage	acc. to IEC 60898-1 400 V AC acc. to IEC 60947-2 400 V AC

Rated Voltage (U _r)	400 V AC
Power Loss	5 W
	at Rated Operating Conditions per Pole 2.5 W
Rated Insulation Voltage (U _i)	acc. to IEC/EN 60664-1 440 V
Operational Voltage	Maximum (Incl. Tolerance) 125 V DC Maximum (Incl. Tolerance) 440 V AC Maximum 440 V AC Maximum 125 V DC Minimum 12 V AC Minimum 12 V DC
Rated Frequency (f)	50 Hz 60 Hz
Rated Short-Circuit Capacity (I _{cn})	(400 V AC) 25 kA
Rated Ultimate Short-Circuit Breaking Capacity (I _{cu})	(400 V AC) 25 kA
Rated Service Short-Circuit Breaking Capacity (I _{cs})	(400 V AC) 12.5 kA
Energy Limiting Class	3
Overvoltage Category	III
Pollution Degree	3
Rated Impulse Withstand Voltage (U _{imp})	4 kV (6.2 kV @ sea level) (5.0 kV @ 2000 m)
Dielectric Test Voltage	50/60 Hz, 1 min: 2 kV
Housing Material	Insulation Group II, RAL 7035
Actuator Material	Insulation Group II, Black, Sealable
Actuator Marking	I / O
Contact Position Indication	Red ON / Green OFF
Degree of Protection	IP20
Remarks	IP40 in enclosure with cover
Electrical Endurance	20000 AC cycle 20000 cycle
Terminal Type	Screw Terminals
Screw Terminal Type	Failsafe Bi-directional Cylinder-lift Terminal
Connecting Capacity	Busbar 10 / 10 mm ² Flexible with Ferrule 0.75 ... 16 mm ² Flexible 0.75 ... 16 mm ² Rigid 0.75 ... 25 mm ² Stranded 0.75 ... 25 mm ²
Tightening Torque	2.8 N·m
Recommended Screw Driver	Pozidriv 2
Mounting on DIN Rail	TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715
Mounting Position	Any
Built-In Depth (t ₂)	69 mm
Installation Size	acc. to DIN 43880 1
Power Supply Connection	Arbitrary

Environmental

Ambient Air Temperature	Operation -25 ... +55 °C Storage -40 ... +70 °C
Reference Ambient Air Temperature	30 °C
Resistance to Shock acc. to IEC 60068-2-27	25g / 2 shocks / 13 ms

Resistance to Vibrations acc. to IEC 60068-2-6	5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Environmental Conditions	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA	480Y/277 V AC
Connecting Capacity UL/CSA	Busbar 18-8 AWG Conductor 18-4 AWG
Tightening Torque UL/CSA	25 in-lb
Interrupting Rating acc. to UL1077	(480 V AC) 10 kA (480Y / 277 V AC) 10 kA

Dimensions

Product Net Width	35 mm
Product Net Depth / Length	69 mm
Product Net Height	88 mm
Product Net Weight	0.28 kg

Container Information

Package Level 1 Units	carton 5 piece
Package Level 1 Width	92 mm
Package Level 1 Depth / Length	183 mm
Package Level 1 Height	80 mm
Package Level 1 Gross Weight	1.45 kg
Package Level 1 EAN	4016779596411

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85362010
E-Number (Finland)	3216090

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CDK403003D0403
Environmental Information	9AKK107680A6947
Instructions and Manuals	2CDS207104P0001
RoHS Information	2CDK403003D0403

Popular Downloads

Data Sheet, Technical Information	9AKK106930A8017
--------------------------------------	-----------------

Classifications

Object Classification Code	F
ETIM 6	EC000042 - Miniature circuit breaker (MCB)
ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
eClass	V11.0 : 27141901
UNSPSC	39121614

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CDS200922R0001	S2C-S/H6R - Contacto auxiliar y señalización	S2C-S/H6R	1	piece
2CDS200912R0001	S2C-H6R - Contacto Auxiliar	S2C-H6R	1	piece
2CDS200936R0001	S2C-H11L - Auxiliary Contact	S2C-H11L	1	piece
2CDS200936R0002	S2C-H20L - Auxiliary Contact	S2C-H20L	1	piece
2CDS200936R0003	S2C-H02L - Auxiliary Contact	S2C-H02L	1	piece
2CDS200946R0001	S2C-H6-11R - Contacto Auxiliar	S2C-H6-11R	1	piece
2CDS200946R0002	S2C-H6-20R - Contacto Auxiliar	S2C-H6-20R	1	piece
2CDS200946R0003	S2C-H6-02R - Contacto Auxiliar	S2C-H6-02R	1	piece
2CDS200909R0001	S2C-A1 - Bobina emisión	S2C-A1	1	piece
2CDS200909R0002	S2C-A2 - Bobina emisión	S2C-A2	1	piece
2CSS200911R0001	S2C-UA 12 DC - Bobina mínima tensión	S2C-UA 12 DC	1	piece
2CSS200911R0002	S2C-UA 24 AC - Bobina mínima tensión	S2C-UA 24 AC	1	piece
2CSS200911R0003	S2C-UA 48 AC - Bobina mínima tensión	S2C-UA 48 AC	1	piece
2CSS200911R0004	S2C-UA 110 AC - Bobina mínima tensión	S2C-UA 110 AC	1	piece
2CSS200911R0005	S2C-UA 230 AC - Bobina mínima tensión	S2C-UA 230 AC	1	piece
2CSS200911R0006	S2C-UA 400 AC - Bobina mínima tensión	S2C-UA 400 AC	1	piece
2CSS200911R0007	S2C-UA 24 DC - Bobina mínima tensión	S2C-UA 24 DC	1	piece
2CSS200911R0008	S2C-UA 48 DC - Bobina mínima tensión	S2C-UA 48 DC	1	piece
2CSS200911R0009	S2C-UA 110 DC - Bobina mínima tensión	S2C-UA 110 DC	1	piece
2CSS200911R0010	S2C-UA 230 DC - Bobina mínima tensión	S2C-UA 230 DC	1	piece
2CSS201997R0013	S2C-CM1 - Mando motor	S2C-CM1	1	piece
2CSS203997R0013	S2C-CM2/3 - Mando motor	S2C-CM2/3	1	piece
2CSS204997R0013	S2C-CM4 - Mando motor	S2C-CM4	1	piece
GHS2001901R0003	S2C-DH - Accesorio mecánico	S2C-DH	1	piece
2CSS200998R0001	S2C-BP - Mechanical tripping device	S2C-BP	1	piece
2CSS200999R0001	S2C-EST - Base enchufable	S2C-EST	1	piece
2CDS200918R0001	S2C-NT - Hand Operated Neutral	S2C-NT	1	piece
2CCA880100R0001	Sensor 80A CMS-100PS	CMS-100PS	1	piece
2CCA880101R0001	Sensor 40A CMS-101PS	CMS-101PS	1	piece
2CCA880102R0001	Sensor 20A CMS-102PS	CMS-102PS	1	piece

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → Miniature Circuit Breakers MCBs

