

PRODUCT-DETAILS

20 EUCBUSB-81-500

20 EUCBUSB-81-500 SCHUKO® USB socket outlet shuttered



Ogólne informacje

Extended Product Type	20 EUCBUSB-81-500
ID Produktu	2CKA002011A6176
Numer EAN	4011395164549
Opis katalogowy	20 EUCBUSB-81-500 SCHUKO® USB socket outlet shuttered
Opis	With screwless terminals. DP (2 P + E) For supply and support of mobile devices via USB-cable. With USB female connector type A. With electronic short-circuit protection. With electronic overload protection. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet.

Charakterystyka zamówienia

E-Number (Finland)	2506191
E-Number (Sweden)	1815005
Numer EAN	4011395164549
Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85366990
ID produktu zamiennego	2CKA002011A6268

Wymiary

Szerokość produktu netto	0.071 m
Wysokość produktu netto	0.071 m

Głębokość produktu netto	0.053 m
Waga produktu netto	0.16 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.088 m
Wysokość opakowania (poziom 1)	0.075 m
Długość opakowania (poziom 1)	0.096 m
Waga opakowania brutto (poziom 1)	160 g
EAN opakowania (poziom 1)	4011395164549

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0 mA
-------------------------------------	------

Dodatkowe informacje

Napięcie pomocnicze AC/DC	250 V AC/DC
Brand / Label	ABB
Kolor	anthracite
Rodzaj podłączenia	Plug Clamp
Stopień ochrony obudowy	IP20
Częstotliwość (f)	50...50 Hz
Materiał	Material quality: Thermoplastic Material: Plastic
Rodzaj montażu	Flush Mounted
Liczba faz	1
Typ produktu	SCHUKO® USB socket outlet
Nazwa produktu	SCHUKO® USB socket outlet shuttered
Product Range	carat®
Prąd znamionowy (I_n)	16 A
Napięcie znamionowe (U_r)	250 V
ID produktu zastąpionego	2011-0-6176
Data RoHS	20160412
Surface Finishing	Surface protection: Untreated Surface finishing: Glossy

Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności - CE	2CKA100000E0546
Dane RoHS	9AKK104295D8727

Klasyfikacje	
ETIM 5	EC000125 - Socket outlet
ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie
Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Axcent → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Dynasty → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Carat → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Future → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Pur Stainless Steel → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Solo → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Produkty niskiego napięcia i systemy → Switch Assortments → Socket Outlets → Socket Outlets with Advanced Functionality → Socket Outlets with Advanced Functionality - Flush Mounted → Socket Outlets With Advanced Functionality

