

PRODUCT-DETAILS

20 EUCBUSB-84-500

20 EUCBUSB-84-500 SCHUKO® USB socket outlet shuttered



General Information

Extended Product Type	20 EUCBUSB-84-500
Product ID	2CKA002011A6179
EAN	4011395164570
Catalog Description	20 EUCBUSB-84-500 SCHUKO® USB socket outlet shuttered
Long Description	With screwless terminals. DP (2 P + E) For supply and support of mobile devices via USB-cable. With USB female connector type A. With electronic short-circuit protection. With electronic overload protection. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet.

Ordering

E-Number (Finland)	2506190
E-Number (Sweden)	1815009
EAN	4011395164570
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990
Replacement Product ID (NEW)	2CKA002011A6274

Dimensions

Product Net Width	0.071 m
Product Net Height	0.071 m
Product Net Depth /	0.053 m

Length

Product Net Weight	0.16 kg
--------------------	---------

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.088 m
Package Level 1 Height	0.075 m
Package Level 1 Depth / Length	0.096 m
Package Level 1 Gross Weight	160 g
Package Level 1 EAN	4011395164570
Package Level 2 Units	10 piece
Package Level 2 Width	0.193 m
Package Level 2 Height	0.116 m
Package Level 2 Depth / Length	0.393 m
Package Level 2 Gross Weight	1.7 kg
Package Level 3 Units	960 piece
Package Level 3 Width	0.8 m
Package Level 3 Height	1.078 m
Package Level 3 Depth / Length	1.2 m
Package Level 3 Gross Weight	184 kg

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0 mA
-------------------------------------	------

Additional Information

Auxiliary Voltage AC/DC	250 V AC/DC
Brand / Label	ABB
Color	studio white
Connection Type	Plug Clamp
Degree of Protection	IP20
Frequency (f)	50...50 Hz
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush Mounted
Number of Phases	1
Product Main Type	SCHUKO® USB socket outlet
Product Name	SCHUKO® USB socket outlet shuttered
Product Range	carat®
Rated Current (I _n)	16 A
Rated Voltage (U _r)	250 V
Replaced Product ID (OLD)	2011-0-6179
RoHS Date	20160412

Surface Finishing

Surface protection: Untreated
Surface finishing: Glossy

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	2CKA100000E0549
RoHS Information	9AKK104295D8727

Classifications	
ETIM 5	EC000125 - Socket outlet
ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Axcent → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Dynasty → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Carat → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Future → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Pur Stainless Steel → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Solo → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality
Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Socket Outlets with Advanced Functionality → Socket Outlets with Advanced Functionality - Flush Mounted → Socket Outlets With Advanced Functionality

