

PRODUCT-DETAILS

20 EUCKS-95-507

20 EUCKS-95-507 SCHUKO® socket outlet shuttered



General Information

Extended Product Type	20 EUCKS-95-507
Product ID	2CKA002013A5338
EAN	4011395160992
Catalog Description	20 EUCKS-95-507 SCHUKO® socket outlet shuttered
Long Description	With screwless terminals. DP (2 P + E)

Ordering

EAN	4011395160992
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990

Dimensions

Product Net Weight	0.07 kg
--------------------	---------

Container Information

Package Level 1 Units	10 piece
Package Level 1 Width	0.158 m
Package Level 1 Height	0.076 m
Package Level 1 Depth /	0.249 m

Length

Package Level 1 Gross

790 g

Weight

Environmental

RoHS Status

Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Short-Circuit Current

0 mA

Rating (SCCR)

Additional Information

Auxiliary Voltage AC/DC

250 V AC/DC

Brand / Label

Busch-Jaeger

Color

château-black

Connection Type

Plug Clamp

Frequency (f)

50...50 Hz

Material

Material quality: Thermoplastic

Material: Plastic

Mounting Type

Flush Mounted

Number of Phases

1

Product Main Type

SCHUKO® socket outlet

Product Name

SCHUKO® socket outlet shuttered

Product Range

carat®

Rated Current (I_N)

16 A

Rated Voltage (U_r)

250 V

Replaced Product ID
(OLD)

2013-0-5338

RoHS Date

20140909

Surface Finishing

Surface protection: Untreated

Surface finishing: Glossy

Certificates and Declarations (Document Number)

Declaration of

2CKA100000E2904

Conformity - CE

RoHS Information

9AKK104295D8727

Classifications

ETIM 5

EC000125 - Socket outlet

ETIM 6

EC000125 - Socket outlet

ETIM 7

EC000125 - Socket outlet

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Basic 55 → Design Basic55 →
CoverPlates (partly incl. Insert) → Single Socket Outlets

Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Single Socket Outlets → Single Socket Outlets -
Flush Mounted → Single Socket Outlets

