

## PRODUCT-DETAILS

# 20 MW-53-500

## 20 MW-53-500 Socket outlet with earthing pin



### General Information

|                       |                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 20 MW-53-500                                                                                                |
| Product ID            | 2CKA002017A0762                                                                                             |
| EAN                   | 4011395993521                                                                                               |
| Catalog Description   | 20 MW-53-500 Socket outlet with earthing pin                                                                |
| Long Description      | With screwless terminals. With hinged lid. Suitable for the countries like Poland, Czech Republic. 2 P + E, |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 4011395993521 |
| Minimum Order Quantity | 1 piece       |
| Customs Tariff Number  | 85366990      |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 0.074 m |
| Product Net Height         | 0.083 m |
| Product Net Depth / Length | 0.055 m |
| Product Net Weight         | 0.12 kg |

### Container Information

|                                |            |
|--------------------------------|------------|
| Package Level 1 Units          | 10 piece   |
| Package Level 1 Width          | 0.184 m    |
| Package Level 1 Height         | 0.116 m    |
| Package Level 1 Depth / Length | 0.315 m    |
| Package Level 1 Gross Weight   | 1.37 kg    |
| Package Level 2 Units          | 100 piece  |
| Package Level 2 Width          | 0.393 m    |
| Package Level 2 Height         | 0.331 m    |
| Package Level 2 Depth / Length | 0.596 m    |
| Package Level 2 Gross Weight   | 14.533 kg  |
| Package Level 3 Units          | 1200 piece |
| Package Level 3 Width          | 0.8 m      |
| Package Level 3 Height         | 1.143 m    |
| Package Level 3 Depth / Length | 1.2 m      |
| Package Level 3 Gross Weight   | 194.396 kg |

## Environmental

|             |                                                                 |
|-------------|-----------------------------------------------------------------|
| RoHS Status | Following EU Directive 2002/95/EC August 18, 2005 and amendment |
|-------------|-----------------------------------------------------------------|

## Technical UL/CSA

|                                     |      |
|-------------------------------------|------|
| Short-Circuit Current Rating (SCCR) | 0 mA |
|-------------------------------------|------|

## Additional Information

|                           |                                                          |
|---------------------------|----------------------------------------------------------|
| Auxiliary Voltage AC/DC   | 250 V AC/DC                                              |
| Brand / Label             | Busch-Jaeger                                             |
| Color                     | grey / blue-green                                        |
| Connection Type           | Plug Clamp                                               |
| Degree of Protection      | IP44                                                     |
| Frequency (f)             | 50...50 Hz                                               |
| Material                  | Material quality: Thermoplastic<br>Material: Plastic     |
| Mounting Type             | Surface Mounted                                          |
| Number of Phases          | 1                                                        |
| Product Main Type         | Socket outlet                                            |
| Product Name              | Socket outlet with earthing pin                          |
| Product Range             | Aluminium die-cast/special devices                       |
| Rated Current ( $I_n$ )   | 16 A                                                     |
| Rated Voltage ( $U_r$ )   | 250 V                                                    |
| Replaced Product ID (OLD) | 2017-0-0762                                              |
| RoHS Date                 | 20140905                                                 |
| Surface Finishing         | Surface protection: Untreated<br>Surface finishing: Matt |

## Certificates and Declarations (Document Number)

|                |                 |
|----------------|-----------------|
| Declaration of | 2CKA100000E3020 |
|----------------|-----------------|

|                  |                 |
|------------------|-----------------|
| Conformity - CE  |                 |
| RoHS Information | 9AKK104295D8727 |

**Classifications**

|               |                                                            |
|---------------|------------------------------------------------------------|
| ETIM 5        | EC000125 - Socket outlet                                   |
| ETIM 6        | EC000125 - Socket outlet                                   |
| ETIM 7        | EC000125 - Socket outlet                                   |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

**Categories**

Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Single Socket Outlets → Single Socket Outlets - Flush Mounted → Single Socket Outlets

Low Voltage Products and Systems → Switch Assortments → Surface Mounted Range → Surface Ranges Waterproof IP44 → Design Ocean → Single Socket Outlets

