

PRODUCT-DETAILS

20 MUCBUSB-82-500

20 MUCBUSB-82-500 Socket outlet with earthing pin



General Information

Extended Product Type	20 MUCBUSB-82-500
Product ID	2CKA002017A0875
EAN	4011395164778
Catalog Description	20 MUCBUSB-82-500 Socket outlet with earthing pin
Long Description	With screwless terminals. Shuttered. DP (2 P + E) For supply and support of mobile devices via USB-cable. With USB female connector type A. With electronic short-circuit protection. With electronic overload protection. Simultaneous charging via USB connection and use of the SCHUKO® socket outlet. Suitable for the countries like Poland, Czech Republic.

Ordering

EAN	4011395164778
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990
Replacement Product ID (NEW)	2CKA002017A1889

Dimensions

Product Net Width	0.071 m
Product Net Height	0.071 m
Product Net Depth / Length	0.053 m
Product Net Weight	0.16 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.088 m
Package Level 1 Height	0.075 m
Package Level 1 Depth / Length	0.096 m
Package Level 1 Gross Weight	160 g
Package Level 1 EAN	4011395164778

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Technical UL/CSA

Short-Circuit Current Rating (SCCR)	0 mA
-------------------------------------	------

Additional Information

Auxiliary Voltage AC/DC	250 V AC/DC
Brand / Label	ABB
Color	ivory white
Connection Type	Plug Clamp
Degree of Protection	IP20
Frequency (f)	50...50 Hz
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush Mounted
Number of Phases	1
Product Main Type	Socket outlet
Product Name	Socket outlet with earthing pin
Product Range	USB charging devices
Rated Current (I_n)	16 A
Rated Voltage (U_r)	250 V
Replaced Product ID (OLD)	2017-0-0875
RoHS Date	20160412
Surface Finishing	Surface protection: Untreated Surface finishing: Glossy

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CKA000073B9557
Declaration of Conformity - CE	2CKA200000E3851
RoHS Information	9AKK104295D8727

Classifications

ETIM 5	EC000125 - Socket outlet
--------	--------------------------

ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Axcent → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Dynasty → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Carat → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Future → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Pur Stainless Steel → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Solo → CoverPlates (partly incl. Insert) → Socket Outlets With Advanced Functionality

Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Socket Outlets with Advanced Functionality → Socket Outlets with Advanced Functionality - Flush Mounted → Socket Outlets With Advanced Functionality

