

0.156 kg

PRODUCT-DETAILS

20 EWSL-54

20 EWSL-54 SCHUKO® socket outlet



General Information	
Extended Product Type	20 EWSL-54
Product ID	2CKA002083A0832
EAN	4011395079621
Catalog Description	20 EWSL-54 SCHUKO® socket outlet
Long Description	With screwless terminals. With security lock in hinged lid. 2 P + E, lockable, 2 keys. Cannot be screwed on or dismounted in closed condition. approx. 200 different locks (unsorted),

Ordering	
EAN	4011395079621
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990
Dimensions	
	0.074 m
Dimensions Product Net Width Product Net Height	0.074 m 0.083 m

Container Information

Length

Product Net Weight

Package Level 1 Units	10 piece
Package Level 1 Width	0.219 m
Package Level 1 Height	0.117 m
Package Level 1 Depth / Length	0.386 m
Package Level 1 Gross Weight	1.864 kg

Environmental

RoHS Status Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Short-Circuit Current 0 mA Rating (SCCR)

Additional Information

Auxiliary Voltage AC/DC	250 V AC/DC
Brand / Label	Busch-Jaeger
Color	alpine white
Connection Type	Plug Clamp
Degree of Protection	IP44
Frequency (f)	5050 Hz
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Surface Mounted
Number of Phases	1
Product Main Type	SCHUKO® socket outlet
Product Name	SCHUKO® socket outlet
Product Range	Surface-mounted IP 44
Rated Current (I _n)	16 A
Rated Voltage (U _r)	250 V
Replaced Product ID (OLD)	2083-0-0832
RoHS Date	20160705
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CKA100000E3250
RoHS Information	9AKK104295D8727

Classifications

ETIM 5	EC000125 - Socket outlet
ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

20 EWSL-54 3

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Socket\ Outlets \rightarrow Single\ Socket\ Outlets \rightarrow Flush\ Mounted \rightarrow Single\ Socket\ Outlets$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Surface\ Mounted\ Range \rightarrow Surface\ Ranges\ Waterproof\ IP44 \rightarrow Design\ Ocean \rightarrow Single\ Socket\ Outlets$

