

PRODUCT-DETAILS

3120 EUCB-884 3120 EUCB-884 FI-SCHUKOMAT, SCHUKO® socket outlet (RCD) with earth leakage circuit breaker



General Information	
Extended Product Type	3120 EUCB-884
Product ID	2CKA003116A0670
EAN	4011395229866
Catalog Description	3120 EUCB-884 FI-SCHUKOMAT, SCHUKO® socket outlet (RCD) with earth leakage circuit breaker
Long Description	Shuttered. DP cut off (P,N) Without PE monitoring. With output terminals for connecting and protecting downsream SCHUKO® socket outlets. Rated actuating current: 30 mA. Release time: ≤ 30 ms. Short-circuit strength: 3000 A (with 25 A GL fuse). Current surge strength: 250 A (8/20) μs. With fixing claws. Rated frequency: 45-60 Hz.

200 / (0/20) με: With fixing claws. Nated inequality: +c	
Ordering	
EAN	4011395229866
Minimum Order Quantity	1 piece
Customs Tariff Number	85366990
Dimensions	
Product Net Weight	0.164 kg

Container Information

Package Level 1 Units 1 piece

Package Level 1 Width	0.088 m
Package Level 1 Height	0.075 m
Package Level 1 Depth / Length	0.096 m
Package Level 1 Gross Weight	164 g
Package Level 1 EAN	4011395229866
Package Level 2 Units	10 piece
Package Level 2 Width	0.18 m
Package Level 2 Height	0.09 m
Package Level 2 Depth / Length	0.385 m
Package Level 2 Gross Weight	1.82 kg

Environmental

RoHS Status Following EU Directive 2002/95/EC August 18, 2005 and amendment

Technical UL/CSA

Short-Circuit Current
Rating (SCCR)

30 mA

Additional Information

Auxiliary Voltage AC/DC	230 V AC/DC
Brand / Label	Busch-Jaeger
Color	studio white matt
Connection Type	Plug Clamp
Degree of Protection	IP20
Frequency (f)	5050 Hz
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush Mounted
Number of Phases	1
Product Main Type	FI-SCHUKOMAT, SCHUKO® socket outlet (RCD)
Product Name	FI-SCHUKOMAT, SCHUKO® socket outlet (RCD) with earth leakage circuit breaker
Product Range	carat®
Rated Current (I _n)	16 A
Rated Voltage (U _r)	230 V
Replaced Product ID (OLD)	3116-0-0670
RoHS Date	20160428
Surface Finishing	Surface protection: Lacquered Surface finishing: Matt

Certificates and Declarations (Document Number)

 Declaration of Conformity - CE
 2CKA200000E4314

 RoHS Information
 9AKK104295D8727

3120 EUCB-884 3

Classifications		
ETIM 5	EC000125 - Socket outlet	
ETIM 6	EC000125 - Socket outlet	
ETIM 7	EC000125 - Socket outlet	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)	

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Busch-Jaeger \rightarrow\ Design\ Busch-Axcent \rightarrow\ CoverPlates\ (partly\ incl.\ Insert) \rightarrow\ Socket\ Outlets\ With\ Advanced\ Functionality$

Low Voltage Products and Systems \rightarrow Switch Assortments \rightarrow Flush Mounted VDE Range - Busch-Jaeger \rightarrow Design Busch-Dynasty \rightarrow CoverPlates (partly incl. Insert) \rightarrow Socket Outlets With Advanced Functionality

Low Voltage Products and Systems \rightarrow Switch Assortments \rightarrow Flush Mounted VDE Range - Busch-Jaeger \rightarrow Design Carat \rightarrow CoverPlates (partly incl. Insert) \rightarrow Socket Outlets With Advanced Functionality

Low Voltage Products and Systems \rightarrow Switch Assortments \rightarrow Flush Mounted VDE Range - Busch-Jaeger \rightarrow Design Future \rightarrow CoverPlates (partly incl. Insert) \rightarrow Socket Outlets With Advanced Functionality

Low Voltage Products and Systems \rightarrow Switch Assortments \rightarrow Flush Mounted VDE Range - Busch-Jaeger \rightarrow Design Pur Stainless Steel \rightarrow CoverPlates (partly incl. Insert) \rightarrow Socket Outlets With Advanced Functionality

Low Voltage Products and Systems \rightarrow Switch Assortments \rightarrow Flush Mounted VDE Range - Busch-Jaeger \rightarrow Design Solo \rightarrow CoverPlates (partly incl. Insert) \rightarrow Socket Outlets With Advanced Functionality

 $Low\ Voltage\ Products\ and\ Systems \to Switch\ Assortments \to Socket\ Outlets \to Socket\ Outlets\ with\ Advanced\ Functionality \to Socket\ Outlets\ With\ Advanced\ Functionality$

