

PRODUCT-DETAILS

6131/31-24-500

6131/31-24-500 Busch-Presence detector premium KNX 12 meters



Общая информация

Тип расширенного изделия	6131/31-24-500
Идентификационный номер изделия	2CKA006132A0348
Европейский товарный код (EAN)	4011395185940
Описание в каталоге	6131/31-24-500 Busch-Presence detector premium KNX 12 meters

Длинное описание

Detection range (for mounting height 2.5 m, 3 m and 4 m): circular. Seated persons Ø: max. 8 m, max. 10 m and max. 14 m. Walking persons Ø: max. 10 m, max. 12 m and max. 16 m. Visible height 23 mm. With 4 channels. For dimming/brightness of the rules to a defined value in a designated collection area. HVAC function for controlling heating and/or cooling systems and ventilation systems in the designated collection area. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light controller with up to two independent channels. Constant light controller with max. 2 outputs for dimming daylight control/rules of two rooflights in the room. Integrated object room temperature controller. 10 freely programmable IR channels (blue and/or white) Incl. 5 logic channels (logic gates, gates, delay and staircase lighting) Evaluation via internal brightness sensor. Weighting of up to 2 external brightness values and the internal brightness sensor possible. The programming button can be activated with the IR transmitter 6010-25 (-500). With integrated KNX bus coupler. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm. Suitable for surface mounting installation. Cannot be installed in British Standard or VDE flushmounted box. Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.

Ordering

Европейский товарный код (EAN)	4011395185940
Номер таможенного тарифа	85365080
Минимальный объем	1 штука

заказа

E-Number (Finland)	2815473
E-Number (Sweden)	1738688

Dimensions

Чистая толщина изделия	0.045 m
Чистая высота изделия	0.091 m
Чистая ширина изделия	0.091 m
Чистый вес изделия	0.081 kg

Container Information

Package Level 1 Units	1 штука
Package Level 1 EAN	4011395185940
Package Level 1 Depth / Length	0.121 m
Package Level 1 Height	0.062 m
Package Level 1 Width	0.096 m
Package Level 1 Gross Weight	146 g

Technical

Compatible Bus Systems	KNX
Степень защиты	IP20
Тип монтажа	Flush Mounted

Certificates and Declarations (Document Number)

Технические данные	2СКА001373В8668
Декларация о соответствии - CE	2СКА100000Е1059
Правила ограничения содержания вредных веществ.RoHS информация	9АКК104295D8727

Environmental

Правила ограничения содержания вредных веществ. RoHS статус	Согласно Директиве ЕС 2002/95/ЕС от 18 августа 2005 г. и поправкам
---	--

Classifications

ETIM 5	EC001582 - Movement sensor for bus system
ETIM 6	EC001582 - Movement sensor for bus system
ETIM 7	EC001582 - Movement sensor for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Категории

Низковольтное оборудование → Home and Building Automation → KNX → Presence Detection → Presence Detectors

