

PRODUCT-DETAILS

6131/50-24-500

6131/50-24-500 Busch-Presence detector

Corridor KNX 30 meters



Ogólne informacje

Extended Product Type	6131/50-24-500
ID Produktu	2CKA006132A0399
Numer EAN	4011395216446
Opis katalogowy	6131/50-24-500 Busch-Presence detector Corridor KNX 30 meters

Opis

Detection range: rectangular. For mounting height of 3 m: frontal toward the detector at a max. of 20 m x 3 m (at a max. of 10 m x 3 m per side). Crosswise toward the detector at a max. of 30 m x 3 m (max. of 15 m x 3m per side). With integrated KNX bus coupler.

Mounting height 27 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Regulation in response to the movement possible. Using the device as presence and/or movement detectors. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. Ceiling mounting on suspended ceilings with spring clamps, on solid ceilings in surface-mounting boxes 6131/39-xxx(-500) or on VDE flush-mounted boxes with intermediate ring for VDE flush-mounted boxes 6131/38-xxx(-500). Suitable for false ceilings with a board thickness from 9 to 25 mm.

Hole size: Ø 68 mm. Cannot be installed in British Standard or VDE flushmounted box.

Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.

Charakterystyka zamówienia

Numer EAN	4011395216446
Kod taryfy celnej	85365080

Minimalna ilość zamówienia	1 sztuka
E-Number (Finland)	2815600
E-Number (Sweden)	1739146

Wymiary

Głębokość produktu netto	0.049 m
Wysokość produktu netto	0.091 m
Szerokość produktu netto	0.091 m
Waga produktu netto	0.117 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
EAN opakowania (poziom 1)	4011395216446
Długość opakowania (poziom 1)	0.121 m
Wysokość opakowania (poziom 1)	0.062 m
Szerokość opakowania (poziom 1)	0.096 m
Waga opakowania brutto (poziom 1)	157 g

Dane techniczne

Compatible Bus Systems	KNX
Stopień ochrony obudowy	IP20
Rodzaj montażu	Flush Mounted

Certyfikaty i deklaracje (Numer dokumentu)

Arkusze danych, informacja techniczna	2CKA001373B8668
Deklaracja zgodności - CE	2CKA100000E1102
Dane RoHS	9AKK104295D8727

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Klasyfikacje

ETIM 5	EC001582 - Movement sensor for bus system
ETIM 6	EC001582 - Movement sensor for bus system
ETIM 7	EC001582 - Movement sensor for bus system

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → Home and Building Automation → KNX → Presence Detection → Presence Detectors

