

PRODUCT-DETAILS

6131/50-24-500

6131/50-24-500 Busch-Presence detector

Corridor KNX 30 meters



Общая информация

Тип расширенного изделия	6131/50-24-500
Идентификационный номер изделия	2CKA006132A0399
Европейский товарный код (EAN)	4011395216446
Описание в каталоге	6131/50-24-500 Busch-Presence detector Corridor KNX 30 meters

Длинное описание

Detection range: rectangular. For mounting height of 3 m: frontal toward the detector at a max. of 20 m x 3 m (at a max. of 10 m x 3 m per side). Crosswise toward the detector at a max. of 30 m x 3 m (max. of 15 m x 3m per side). With integrated KNX bus coupler.

Mounting height 27 mm. With 2 channels. Targeted for connection and disconnection of lights bands depending on the room brightness. Regulation in response to the movement possible. Using the device as presence and/or movement detectors. Detectors application with 2 power off stages. Detectors application with integrated monitoring function. Constant light switch with up to two independent channels. Constant light switch with max. 2 outputs for brightness-dependent switching of two light bands in the area. Ceiling mounting on suspended ceilings with spring clamps, on solid ceilings in surface-mounting boxes 6131/39-xxx(-500) or on VDE flush-mounted boxes with intermediate ring for VDE flush-mounted boxes 6131/38-xxx(-500). Suitable for false ceilings with a board thickness from 9 to 25 mm.

Hole size: Ø 68 mm. Cannot be installed in British Standard or VDE flushmounted box.

Recommendation: Installation housing from Kaiser HaloX-O (Art.no. 1290-40) with corresponding cover plates (1290-47 or 1290-85 for fair faced concrete) or IBTronic H120-68 from Spelsberg.

Ordering

Европейский товарный код (EAN)	4011395216446
--------------------------------	---------------

Номер таможенного тарифа	85365080
Минимальный объем заказа	1 штука
E-Number (Finland)	2815600
E-Number (Sweden)	1739146

Dimensions

Чистая толщина изделия	0.049 m
Чистая высота изделия	0.091 m
Чистая ширина изделия	0.091 m
Чистый вес изделия	0.117 kg

Container Information

Package Level 1 Units	1 штука
Package Level 1 EAN	4011395216446
Package Level 1 Depth / Length	0.121 m
Package Level 1 Height	0.062 m
Package Level 1 Width	0.096 m
Package Level 1 Gross Weight	157 g

Technical

Compatible Bus Systems	KNX
Степень защиты	IP20
Тип монтажа	Flush Mounted

Certificates and Declarations (Document Number)

Технические данные	2CKA001373B8668
Декларация о соответствии - CE	2CKA100000E1102
Правила ограничения содержания вредных веществ.RoHS информация	9AKK104295D8727

Environmental

Правила ограничения содержания вредных веществ. RoHS статус	Согласно Директиве EC 2002/95/EC от 18 августа 2005 г. и поправкам
---	--

Classifications

ETIM 5	EC001582 - Movement sensor for bus system
--------	---

ETIM 6	EC001582 - Movement sensor for bus system
ETIM 7	EC001582 - Movement sensor for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Категории

Низковольтное оборудование → Home and Building Automation → KNX → Presence Detection → Presence Detectors

