

PRODUCT-DETAILS

6108/18-500

6108/18-500 Room thermostat with display Heating/cooling operation



General Information

Extended Product Type	6108/18-500
Product ID	2CKA006134A0319
EAN	4011395211014
Catalog Description	6108/18-500 Room thermostat with display Heating/cooling operation
Long Description	Control element with room thermostat function for triggering the heating, ventilation and fan-coil actuators. For controlling commercially available valve drives. For contacting cover plate 6236-xxx. With integrated temperature sensor. With display of set-value temperature. Master/slave configuration. With base-load operation. The bus can be connected via enclosed terminal block. Class of temperature controller 1 Contribution to space heating energy efficiency 1,0%.

Ordering

EAN	4011395211014
Customs Tariff Number	90321020
Minimum Order Quantity	1 piece
E-Number (Finland)	2815559
E-Number (Sweden)	1739088

Dimensions

Product Net Depth / Length	0.023 m
Product Net Height	0.05 m
Product Net Width	0.045 m

Product Net Weight	0.08 kg
--------------------	---------

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	4011395211014
Package Level 1 Depth / Length	0.073 m
Package Level 1 Height	0.073 m
Package Level 1 Width	0.036 m
Package Level 1 Gross Weight	80 g

Technical

Compatible Bus Systems	KNX
Degree of Protection	IP20
Mounting Type	Flush Mounted
Screen Size	1 in

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CKA001373B8913
Declaration of Conformity - CE	2CKA100000E1140
RoHS Information	9AKK104295D8727

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 5	EC001101 - Room temperature controller for bus system
ETIM 6	EC001101 - Room temperature controller for bus system
ETIM 7	EC001101 - Room temperature controller for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Home and Building Automation → KNX → User Operation - Push Button Coupling Units → Push Button Coupling Units

