


PRODUCT-DETAILS

TR/U 1.1

TR/U 1.1 Transponder reader



General Information

Extended Product Type	TR/U 1.1
Product ID	2CKA006137A0022
EAN	4011395219829
Catalog Description	TR/U 1.1 Transponder reader
Long Description	For ABB i-bus® KNX External supply: 12-24 AC/DC Absorption: max 10 mA from the BUS. External supply to be sized for 3-W peak. Number of outputs: 1 bistable relay 4A @24V AC/DC. Number of inputs: 1 on the rear side, NO, max. connection length 10m. Ambient conditions: class 3k5 (indoor rooms and dry rooms). Relative humidity: max 90% (non condensating).

Ordering

EAN	4011395219829
Minimum Order Quantity	1 piece

Dimensions

Product Net Height	0.044 m
Product Net Width	0.044 m
Product Net Weight	999 kg

Technical

Degree of Protection	IP20
----------------------	------

Mounting Type

Flush Mounted

Classifications

ETIM 5	EC001101 - Room temperature controller for bus system
ETIM 6	EC001101 - Room temperature controller for bus system
ETIM 7	EC001101 - Room temperature controller for bus system

Categories

Low Voltage Products and Systems → Home and Building Automation → KNX → User Operation - tacteo → Thermostats

