


PRODUCT-DETAILS

TR/U 1.1

TR/U 1.1 Transponder reader



Ogólne informacje

Extended Product Type	TR/U 1.1
ID Produktu	2CKA006137A0022
Numer EAN	4011395219829
Opis katalogowy	TR/U 1.1 Transponder reader
Opis	For ABB i-bus® KNX External supply: 12-24 AC/DC Absorption: max 10 mA from the BUS. External supply to be sized for 3-W peak. Number of outputs: 1 bistable relay 4A @24V AC/DC. Number of inputs: 1 on the rear side, NO, max. connection length 10m. Ambient conditions: class 3k5 (indoor rooms and dry rooms). Relative humidity: max 90% (non condensating).

Charakterystyka zamówienia

Numer EAN	4011395219829
Minimalna ilość zamówienia	1 sztuka

Wymiary

Wysokość produktu netto	0.044 m
Szerokość produktu netto	0.044 m
Waga produktu netto	999 kg

Dane techniczne	
Stopień ochrony obudowy	IP20
Rodzaj montażu	Flush Mounted

Klasyfikacje	
ETIM 5	EC001101 - Room temperature controller for bus system
ETIM 6	EC001101 - Room temperature controller for bus system
ETIM 7	EC001101 - Room temperature controller for bus system

Kategorie	
Produkty niskiego napięcia i systemy → Home and Building Automation → KNX → User Operation - tacteo → Thermostats	

