

PRODUCT-DETAILS

SBA-F-1.1.1-WL

SBA-F-1.1.1-WL Sensor/blind actuator,
1/1gang, wireless for ABB-free@home®



General Information

Extended Product Type	SBA-F-1.1.1-WL
Product ID	2CKA006200A0079
EAN	4011395215685
Catalog Description	SBA-F-1.1.1-WL Sensor/blind actuator, 1/1gang, wireless for ABB-free@home®
Long Description	For controlling blind or awning motors. Communication with the free@home system is carried out wireless. With integrated blind actuator. Blind function is available also without prior programming (pre-configured). Configuration can be changed later via the web interface (groups, scenes, etc.). For contacting 1gang rocker 6230-10-xxx, 6231-10-xxx, 6232-10-xxx, 6233-10-xxx und 6234-10-xxx. 3 wire connection (neutral conductor required). With two 230 V extension unit inputs (Up/Down). With fixing claws.

Ordering

EAN	4011395215685
Customs Tariff Number	85389091
Minimum Order Quantity	1 piece
E-Number (Finland)	2815617
E-Number (Sweden)	1701231

Dimensions

Product Net Depth / Length	0.045 m
Product Net Height	0.071 m

Product Net Width	0.071 m
Product Net Weight	0.105 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	4011395215685
Package Level 1 Depth / Length	0.158 m
Package Level 1 Height	0.065 m
Package Level 1 Width	0.086 m
Package Level 1 Gross Weight	186 g

Technical

Degree of Protection	IP20
Mounting Type	Flush Mounted

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CKA001473B9110
Declaration of Conformity - CE	2CKA100000E2644
RoHS Information	9AKK104295D8727

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 5	EC001330 - Shutting actuator for bus system
ETIM 6	EC001330 - Shutting actuator for bus system
ETIM 7	EC001330 - Shutting actuator for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Home and Building Automation → free@home → Shading Control → Blind Actuators 230 V AC

