

PRODUCT-DETAILS

## TB/U12.8.1-CG

## TB/U12.8.1-CG Touch control element, 12gang Standard customization



General Information	
Extended Product Type	TB/U12.8.1-CG
Product ID	2CKA006300A1544
EAN	4011395230787
Catalog Description	TB/U12.8.1-CG Touch control element, 12gang Standard customization
Long Description	Ordering possible only in connection with the design ID. The icons and/or texts are configured by means of a web configuration tool. Freely configurable multifunction control element. With integrated KNX bus coupler. With integrated temperature sensor. With integrated proximity function. Push switch function: switching / dimming / blind / sending values / scenes etc. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. The bus connection is provided via the enclosed bus terminal. Number of bus subscribers: 1

Ordering	
EAN	4011395230787
Customs Tariff Number	85365080
Minimum Order Quantity	1 piece
E-Number (Finland)	2814637
E-Number (Sweden)	1739656

Dimensions	
Product Net Height	0.086 m
Product Net Width	0.157 m

Product Net Weight 0.168 kg

Container Information	
Package Level 1 Units	1 piece
Package Level 1 EAN	4011395230787
Package Level 1 Depth / Length	0.18 m
Package Level 1 Height	0.076 m
Package Level 1 Width	0.15 m
Package Level 1 Gross Weight	311 g

Technical	
Compatible Bus Systems	KNX
Degree of Protection	IP20
Mounting Type	Surface Mounted

Certificates and Declarations (Document Number)	
Declaration of	2CKA100000E2529
Conformity - CE	
RoHS Information	9AKK104295D8727

Environmental	
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Classifications	
ETIM 5	EC000672 - Touch sensor for bus system
ETIM 6	EC000672 - Touch sensor for bus system
ETIM 7	EC000672 - Touch sensor for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Home\ and\ Building\ Automation \rightarrow KNX \rightarrow User\ Operation\ -\ tacteo \rightarrow 12\ fold$ 

TB/U12.8.1-CG 3

