


PRODUCT-DETAILS

TB/U12.7.11-CG

TB/U12.7.11-CG Touch control element, 12gang Standard customization



Ogólne informacje

Extended Product Type	TB/U12.7.11-CG
ID Produktu	2CKA006300A1563
Numer EAN	4011395230992
Opis katalogowy	TB/U12.7.11-CG Touch control element, 12gang Standard customization
Opis	Ordering possible only in connection with the design ID. The icons and/or texts are configured by means of a web configuration tool. Freely configurable multifunction control element. With integrated KNX bus coupler. With integrated temperature sensor. With integrated proximity function. Push switch function: switching / dimming / blind / sending values / scenes etc. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. The bus connection is provided via the enclosed bus terminal. Number of bus subscribers: 1

Charakterystyka zamówienia

Numer EAN	4011395230992
Kod taryfy celnej	85365080
Minimalna ilość zamówienia	1 sztuka

Wymiary

Wysokość produktu netto	0.157 m
Szerokość produktu netto	0.086 m
Waga produktu netto	0.169 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
EAN opakowania (poziom 1)	4011395230992
Długość opakowania (poziom 1)	0.18 m
Wysokość opakowania (poziom 1)	0.076 m
Szerokość opakowania (poziom 1)	0.15 m
Waga opakowania brutto (poziom 1)	311 g

Dane techniczne

Compatible Bus Systems	KNX
Stopień ochrony obudowy	IP20
Rodzaj montażu	Surface Mounted

Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności - CE	2CKA100000E2540
Dane RoHS	9AKK104295D8727

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Klasyfikacje

ETIM 5	EC000672 - Touch sensor for bus system
ETIM 6	EC000672 - Touch sensor for bus system
ETIM 7	EC000672 - Touch sensor for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → Home and Building Automation → KNX → User Operation - tacteo → 12 fold

