


PRODUCT-DETAILS

TB/U1.3.1-CG

TB/U1.3.1-CG Touch control element, 1gang Standard customization



General Information

Extended Product Type	TB/U1.3.1-CG
Product ID	2CKA006300A1590
EAN	4011395231289
Catalog Description	TB/U1.3.1-CG Touch control element, 1gang Standard customization
Long Description	Ordering possible only in connection with the design ID. The icons and/or texts are configured by means of a web configuration tool. Freely configurable multifunction control element. With integrated KNX bus coupler. With integrated temperature sensor. With integrated proximity function. Push switch function: switching / dimming / blind / sending values / scenes etc. Support of KNX functions through innovative colour concept (yellow=lighting, blue=blind, orange=RTC, magenta=scene and white=neutral/no function assigned) or standard illumination red/green. The bus connection is provided via the enclosed bus terminal. Number of bus subscribers: 1

Ordering

EAN	4011395231289
Customs Tariff Number	85365080
Minimum Order Quantity	1 piece
E-Number (Finland)	2814652

Dimensions

Product Net Height	0.086 m
Product Net Width	0.115 m
Product Net Weight	0.291 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 EAN	4011395231289
Package Level 1 Depth / Length	0.18 m
Package Level 1 Height	0.076 m
Package Level 1 Width	0.15 m
Package Level 1 Gross Weight	291 g

Technical

Compatible Bus Systems	KNX
Degree of Protection	IP20
Mounting Type	Surface Mounted

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CKA100000E2555
RoHS Information	9AKK104295D8727

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Classifications

ETIM 5	EC000672 - Touch sensor for bus system
ETIM 6	EC000672 - Touch sensor for bus system
ETIM 7	EC000672 - Touch sensor for bus system
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Home and Building Automation → KNX → User Operation - tacteo → 1 fold

