

PRODUCT-DETAILS

6480-84-500

6480-84-500 Busch-powerDock complete set with lightning connector



Ogólne informacje

Extended Product Type	6480-84-500
ID Produktu	2CKA006400A0045
Numer EAN	4011395224618
Opis katalogowy	6480-84-500 Busch-powerDock complete set with lightning connector

Opis	Complete set ready to install for charging mobile terminal devices with Apple lightning connection. Makes possible fast charging of the mobile terminal device. For iPhone XS Max, iPhone XS, iPhone XR, iPhone X. For iPhone 8 Plus, iPhone 8. For iPhone 7 Plus, iPhone 7. For iPhone SE. For iPhone 6s Plus, iPhone 6s, iPhone 6 Plus, iPhone 6. For iPhone 5s, iPhone 5c, iPhone 5. For iPod touch (6th generation), iPod touch (5th generation), iPod nano (7th generation). Suitable for use with protective covers certified by Apple. Consisting of Busch-powerDock insert 6473 U. Consisting of Busch-powerDock charging cradle with lightning connection 6473. Consisting of the cover plate for the Busch-powerDock charging cradle. Consisting of 1gang future® linear cover frames.
------	--

Charakterystyka zamówienia

Numer EAN	4011395224618
Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85044055

Wymiary

Szerokość produktu netto	0.081 m
Wysokość produktu netto	0.081 m
Głębokość produktu netto	0.074 m
Waga produktu netto	0.288 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.1 m
Wysokość opakowania (poziom 1)	0.089 m
Długość opakowania (poziom 1)	0.179 m
Waga opakowania brutto (poziom 1)	288 g
EAN opakowania (poziom 1)	4011395224618
Jednostka opakowania (poziom 2)	10 sztuka
Szerokość opakowania (poziom 2)	0.368 m
Wysokość opakowania (poziom 2)	0.102 m
Długość opakowania (poziom 2)	0.51 m
Jednostka opakowania (poziom 3)	360 sztuka
Szerokość opakowania (poziom 3)	0.8 m
Wysokość opakowania (poziom 3)	1.072 m
Długość opakowania (poziom 3)	1.2 m

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Dodatkowe informacje

Napięcie pomocnicze AC/DC	100 V AC/DC 230 V AC/DC
Kolor	studio white
Rodzaj podłączenia	Pluggable
Stopień ochrony obudowy	IP20
Napięcie wejściowe (U_{in})	100...240 V
Rodzaj montażu	Flush Mounted
Prąd wyjściowy	2100 mA
Napięcie wyjściowe (U_{out})	5...5 V

Typ produktu	Busch-powerDock complete set with lightning connector
Nazwa produktu	Busch-powerDock complete set with lightning connector
Product Range	USB charging devices
ID produktu zastąpionego	6400-0-0045
Data RoHS	20160315

Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności - CE	2CKA100000E0639
Dane RoHS	9AKK104295D8727

Klasyfikacje

ETIM 5	EC001781 - Power supply consumer electronics
ETIM 6	EC001781 - Power supply consumer electronics
ETIM 7	EC001781 - Power supply consumer electronics
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → Switch Assortments → Charging Devices → Charging Devices → Charging Devices - Flush Mounted → Charging Devices

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Axcent → CoverPlates (partly incl. Insert) → Charging Devices

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Dynasty → CoverPlates (partly incl. Insert) → Charging Devices

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Carat → CoverPlates (partly incl. Insert) → Charging Devices

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Future → CoverPlates (partly incl. Insert) → Charging Devices

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Pur Stainless Steel → CoverPlates (partly incl. Insert) → Charging Devices

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Solo → CoverPlates (partly incl. Insert) → Charging Devices

