

PRODUCT-DETAILS

6526 U-500

6526 U-500 Busch-touch dimmer Flush-mounted, LED, 2-100 W



Ogólne informacje

Extended Product Type	6526 U-500
ID Produktu	2CKA006512A0323
Numer EAN	4011395196045
Opis katalogowy	6526 U-500 Busch-touch dimmer Flush-mounted, LED, 2-100 W

Opis	Touch dimmer. 2-wire connection (neutral conductor not required) Neutral conductor optionally connectable (recommended for the connection of low loads < 10 W/VA). Optimised for dimming of retrofit LED lamps (LEDi). For incandescent lamps, 230V tungsten halogen lamps and low-voltage halogen lamps with conventional transformers or electronic transformers and dimmable halogen energy-saving lamps. Mix operation of LEDi with conventional loads possible. With adjustable minimum brightness. The minimum brightness for the leading edge control can be adjusted using the potentiometer. The potentiometer at the left limit stop corresponds with the trailing edge control mode. Low-noise level by MOSFET transistors. With electronic short-circuit protection. With electronic overload protection. With light-level memory and minimum brightness memory. Operation also possible via conventional push buttons (2020 US, 2021/6 UK). Without control cover. For control cover with control lamp 6543-xxx-10x. For Busch-Remote control IR control cover 6066-xxx-10x. For comfort timer control element 6455-101-500. For Busch-Watchdog Presence tech 6813-xxx-101 und 6813/11-xxx. Nominal power: 2 - 100 W/VA (retrofit LED loads). Nominal power: 10 - 200 W/VA (non-LED loads).
------	--

Charakterystyka zamówienia

E-Number (Finland)	2619347
E-Number (Sweden)	1360233
Numer EAN	4011395196045
Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85365080

ID produktu zamiennego

2CKA006500A0013

Wymiary

Szerokość produktu netto	0.071 m
Wysokość produktu netto	0.071 m
Głębokość produktu netto	0.032 m
Waga produktu netto	0.114 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.092 m
Wysokość opakowania (poziom 1)	0.058 m
Długość opakowania (poziom 1)	0.078 m
Waga opakowania brutto (poziom 1)	114 g
EAN opakowania (poziom 1)	4011395196045
Jednostka opakowania (poziom 2)	10 sztuka
Szerokość opakowania (poziom 2)	0.168 m
Wysokość opakowania (poziom 2)	0.112 m
Długość opakowania (poziom 2)	0.298 m
Waga opakowania brutto (poziom 2)	1.14 kg

Normy środowiskowe

Status RoHS

Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami

Dodatkowe informacje

Typ napędu	Touch control button
Napięcie pomocnicze AC/DC	230 V AC/DC
Brand / Label	ABB
Rodzaj podłączenia	Screw
Stopień ochrony obudowy	IP20
Częstotliwość (f)	50...60 Hz
Rodzaj obciążenia	Universal and LED Retrofit
Materiał	Metal
Rodzaj montażu	Flush Mounted
Number of Outputs	1
Typ produktu	Busch-touch dimmer
Nazwa produktu	Busch-touch dimmer Flush-mounted, LED, 2-100 W
Product Range	Flush-mounted installation boxes and inserts
Napięcie znamionowe (U _r)	207...253 V
ID produktu zastąpionego	6512-0-0323

Data RoHS	20160628
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certyfikaty i deklaracje (Numer dokumentu)

Deklaracja zgodności - CE	2CKA100000E1611
Dane RoHS	9AKK104295D8727

Klasyfikacje

ETIM 5	EC000025 - Dimmer
ETIM 6	EC000025 - Dimmer
ETIM 7	EC000025 - Dimmer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → StandAlone Electronics → Presence Detector → Presence Tec Series → Actuators → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Basic 55 → Design Basic55 → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Allwetter 44 (IP 44) → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Alpha → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Axcent → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Balance SI → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Busch-Dynasty → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Carat → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Future → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Impuls → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Pur Stainless Steel → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design SI → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Busch-Jaeger → Design Solo → Flush Mounted Inserts → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Light / LoadControl → Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI) → Push Button Dimmer - Flush Mounted → Dimmer Inserts

Produkty niskiego napięcia i systemy → Switch Assortments → Light / LoadControl → Movement Detectors → Movement Detectors - Flush Mounted → Dimmer Inserts

