

## PRODUCT-DETAILS

# 6819/30-24-500

## 6819/30-24-500 Busch-Presence detector Universal, relay 12 meters



### Ogólne informacje

|                       |                                                                   |
|-----------------------|-------------------------------------------------------------------|
| Extended Product Type | 6819/30-24-500                                                    |
| ID Produktu           | 2CKA006800A2735                                                   |
| Numer EAN             | 4011395217566                                                     |
| Opis katalogowy       | 6819/30-24-500 Busch-Presence detector Universal, relay 12 meters |

### Opis

Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With power relays for LED operation. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

### Charakterystyka zamówienia

|                    |               |
|--------------------|---------------|
| E-Number (Finland) | 2619381       |
| E-Number (Sweden)  | 1301053       |
| Numer EAN          | 4011395217566 |

|                            |          |
|----------------------------|----------|
| Minimalna ilość zamówienia | 1 sztuka |
| Kod taryfy celnej          | 85365080 |

## Wymiary

|                          |         |
|--------------------------|---------|
| Szerokość produktu netto | 0.094 m |
| Wysokość produktu netto  | 0.094 m |
| Głębokość produktu netto | 0.072 m |
| Waga produktu netto      | 0.16 kg |

## Informacje o pakowaniu

|                                   |               |
|-----------------------------------|---------------|
| Jednostka opakowania (poziom 1)   | 1 sztuka      |
| Szerokość opakowania (poziom 1)   | 0.141 m       |
| Wysokość opakowania (poziom 1)    | 0.095 m       |
| Długość opakowania (poziom 1)     | 0.165 m       |
| Waga opakowania brutto (poziom 1) | 306 g         |
| EAN opakowania (poziom 1)         | 4011395217566 |

## Normy środowiskowe

|             |                                                                 |
|-------------|-----------------------------------------------------------------|
| Status RoHS | Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami |
|-------------|-----------------------------------------------------------------|

## Dodatkowe informacje

|                                       |                                                      |
|---------------------------------------|------------------------------------------------------|
| Napięcie pomocnicze AC/DC             | 110 V AC/DC<br>230 V AC/DC                           |
| Brand / Label                         | ABB                                                  |
| Kolor                                 | studio white matt                                    |
| Rodzaj podłączenia                    | Screw                                                |
| Zakres prądowy                        | Maximum 800 A                                        |
| Stopień ochrony obudowy               | IP40                                                 |
| Częstotliwość (f)                     | 50...60 Hz                                           |
| Illuminance                           | 5...2000 lx                                          |
| Materiał                              | Material quality: Thermoplastic<br>Material: Plastic |
| Rodzaj montażu                        | Flush Mounted                                        |
| Number of Outputs                     | 1                                                    |
| Typ produktu                          | Busch-Presence detector Universal, relay             |
| Nazwa produktu                        | Busch-Presence detector Universal, relay 12 meters   |
| Product Range                         | Presence detector                                    |
| Napięcie znamionowe (U <sub>r</sub> ) | 230 V                                                |

Data RoHS

20150724

Surface Finishing

Surface protection: Untreated  
Surface finishing: Matt

---

## Certyfikaty i deklaracje (Numer dokumentu)

|                                       |                 |
|---------------------------------------|-----------------|
| Arkusze danych, informacja techniczna | 2CKA001473B9577 |
| Deklaracja zgodności - CE             | 2CKA100000E0690 |
| Dane RoHS                             | 9AKK104295D8727 |

---

## Klasyfikacje

|               |                                                            |
|---------------|------------------------------------------------------------|
| ETIM 5        | EC000133 - Movement sensor complete                        |
| ETIM 6        | EC000133 - Movement sensor complete                        |
| ETIM 7        | EC000133 - Movement sensor complete                        |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |

---

## Kategorie

Produkty niskiego napięcia i systemy → StandAlone Electronics → Presence Detector → Presence Detector Series → IR Controlled Devices (Master) → Presence Detector Universal, Relay

