

PRODUCT-DETAILS

6817/32-24-500

6817/32-24-500 Busch-Presence detector Universal, e-contact 12 meters



General Information	
Extended Product Type	6817/32-24-500
Product ID	2CKA006800A2739
EAN	4011395217610
Catalog Description	6817/32-24-500 Busch-Presence detector Universal, e-contact 12 meters
Long Description	Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With electronic switch contact for LED operation. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Switch-off delay: approx. 1 min 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Ordering	
E-Number (Finland)	2619383
E-Number (Sweden)	1301055
EAN	4011395217610
Minimum Order Quantity	1 piece

Customs Tariff Number 85365080

2

Dimensions	
Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth / Length	0.059 m
Product Net Weight	0.13 kg

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	136 g
Package Level 1 EAN	4011395217610

Environmental	
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information	
Auxiliary Voltage AC/DC	110 V AC/DC 230 V AC/DC
Brand / Label	ABB
Color	studio white matt
Connection Type	Plug Clamp
Current Range	Maximum 350 A
Degree of Protection	IP40
Frequency (f)	5060 Hz
Illuminance	52000 lx
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush Mounted
Number of Outputs	1
Product Main Type	Busch-Presence detector Universal, e-contact
Product Name	Busch-Presence detector Universal, e-contact 12 meters
Product Range	Movement detector
Rated Voltage (U _r)	230 V
RoHS Date	20150724
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	2CKA100000E0694
RoHS Information	9AKK104295D8727

6817/32-24-500

Classifications	
ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems \rightarrow StandAlone\ Electronics \rightarrow Presence\ Detector \rightarrow Presence\ Detector\ Series \rightarrow IR\ Controlled\ Devices\ (Master) \rightarrow Presence\ Detector\ Universal,\ e\ Contact$

