

PRODUCT-DETAILS

6819/55-24-500

6819/55-24-500 Busch-Presence detector Corridor BT, DALI 30 metres



Общая информация

Тип расширенного изделия	6819/55-24-500
Идентификационный номер изделия	2CKA006800A2749
Европейский товарный код (EAN)	4011395217726
Описание в каталоге	6819/55-24-500 Busch-Presence detector Corridor BT, DALI 30 metres

Длинное описание

Master presence detector with mixed light measurement. For regulating and switching of DALI operating devices that depend on brightness and movement. For DALI broadcast operation (central telegram). Supplies the required voltage for additional DALI operating units and controllers. Suitable for up to 45 DALI operating devices. For changing the colour temperature of >tunable white< lamps, which meet DALI Standard IEC 62386-209 (Device Type 8). Colour temperature can then be set between 2,700 K - 6,500 K. With additional switching output for the activation of heating, air conditioning and ventilation or for switching additional loads (e.g. panel light). Configuration possible up to the complete deactivation of the DALI operating devices. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 30 m x 3 m, frontal 20 m x 3 m. Extension of the detection range by means of master/slave combination. Mounting height 27 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With time-controlled basic illumination function. With selectable warm-up function for fluorescent lamps. With 2-step automatic switch-off (according to EnEV / EN 15232). With time-controlled night anti-glare function. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor).

Ordering

E-Number (Finland)	2619391
E-Number (Sweden)	1301060
Европейский товарный код (EAN)	4011395217726
Минимальный объем заказа	1 штука
Номер таможенного тарифа	85365080

Dimensions

Чистая ширина изделия	0.094 m
Чистая высота изделия	0.094 m
Чистая толщина изделия	0.087 m
Чистый вес изделия	0.163 kg

Container Information

Package Level 1 Units	1 штука
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	337 g
Package Level 1 EAN	4011395217726

Environmental

Правила ограничения содержания вредных веществ. RoHS статус	Согласно Директиве EC 2002/95/EC от 18 августа 2005 г. и поправкам
---	--

Additional Information

Вспомогательное напряжение AC/DC	110 V AC/DC 230 V AC/DC
Торговая марка/ярлык	ABB
Цвет	studio white matt
Тип подключаемой схемы	Plug Clamp
Диапазон тока	Maximum 800 A
Степень защиты	IP40
Частота (f)	50...60 Hz
Illuminance	5...2000 lx
Материалы	Material quality: Thermoplastic Material: Plastic
Тип монтажа	Flush Mounted
Количество выходов	1
Основной тип изделия	Busch-Presence detector Corridor BT, DALI

Название изделия	Busch-Presence detector Corridor BT, DALI 30 metres
Номенклатура изделий	Movement detector
Номинальное напряжение (U _r)	230 V
Правила ограничения содержания вредных веществ RoHS данные	20150724
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)

Технические данные	2CKA001473B9577
Декларация о соответствии - CE	2CKA200000E6496
Правила ограничения содержания вредных веществ RoHS информация	9AKK104295D8727

Classifications

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Категории

Низковольтное оборудование → StandAlone Electronics → Presence Detector → Presence Detector Series → Bluetooth Controlled Devices (Master) → Presence Detector Corridor BT, DALI

