

PRODUCT-DETAILS

6819/59-24-500

6819/59-24-500 Busch-Presence detector Corridor, slave, DALI 30 metres



General Information

Extended Product Type	6819/59-24-500
Product ID	2CKA006800A2761
EAN	4011395217856
Catalog Description	6819/59-24-500 Busch-Presence detector Corridor, slave, DALI 30 metres
Long Description	DALI slave presence detector for extension of the detection range of DALI master presence detectors. For the supply of operating voltage via the DALI master. Power consumption on the DALI bus: max. 10 mA, corresponds to approx. 5 DALI operating devices. The communication with the DALI master is carried out via the DALI interface. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 24 m x 3 m, frontal/lengthways to the detector 14 m x 3 m. Mounting height 27 mm. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Surveillance density: 92 sectors with 368 switching segments. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.

Ordering

E-Number (Finland)	2619394
E-Number (Sweden)	1301062
EAN	4011395217856
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	0.094 m
Product Net Height	0.094 m
Product Net Depth / Length	0.076 m
Product Net Weight	0.152 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.141 m
Package Level 1 Height	0.095 m
Package Level 1 Depth / Length	0.165 m
Package Level 1 Gross Weight	282 g
Package Level 1 EAN	4011395217856

Environmental

RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment
-------------	---

Additional Information

Auxiliary Voltage AC/DC	9.5 V AC/DC 22.5 V AC/DC
Brand / Label	ABB
Color	studio white matt
Connection Type	Plug Clamp
Degree of Protection	IP40
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush Mounted
Product Main Type	Busch-Presence detector Corridor, slave, DALI
Product Name	Busch-Presence detector Corridor, slave, DALI 30 metres
Product Range	Movement detector
Rated Voltage (U _r)	16 V
RoHS Date	20150724
Surface Finishing	Surface protection: Untreated Surface finishing: Matt

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	2CKA001473B9577
Declaration of Conformity - CE	2CKA200000E6506
RoHS Information	9AKK104295D8727

Classifications

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → StandAlone Electronics → Presence Detector → Presence Detector Series → Slave Devices → Presence Detector Corridor, DALI Slave

