

PRODUCT-DETAILS

6817/32-183-500

6817/32-183-500 Busch-Presence detector Universal, e-contact 12 meters



Ogólne informacje

Extended Product Type	6817/32-183-500
ID Produktu	2CKA006800A2773
Numer EAN	4011395217979
Opis katalogowy	6817/32-183-500 Busch-Presence detector Universal, e-contact 12 meters

Opis	Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With electronic switch contact for LED operation. Detection range (for installation height of 3 m): circular Seated persons: up to Ø 10 m, walking persons: up to Ø 12 m. Extension of the detection range by means of master/slave combination. Visible height 23 mm. For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With brightness-independent test mode for evaluating the detection zone. With teach-in function of the brightness switching threshold, IR service remote control required. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 72 sectors with 640 switching segments. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. Remote control possible via IR service remote control 6843. Suitable for false ceilings with a board thickness from 9 to 25 mm. Hole size: Ø 68 mm.
------	---

Charakterystyka zamówienia

Numer EAN	4011395217979
Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85365080

Wymiary

Szerokość produktu netto	0.094 m
Wysokość produktu netto	0.094 m
Głębokość produktu netto	0.059 m
Waga produktu netto	0.13 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.141 m
Wysokość opakowania (poziom 1)	0.095 m
Długość opakowania (poziom 1)	0.165 m
Waga opakowania brutto (poziom 1)	298 g
EAN opakowania (poziom 1)	4011395217979

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Dodatkowe informacje

Napięcie pomocnicze AC/DC	110 V AC/DC 230 V AC/DC
Brand / Label	ABB
Kolor	aluminium silver
Rodzaj podłączenia	Plug Clamp
Zakres prądowy	Maximum 350 A
Stopień ochrony obudowy	IP40
Częstotliwość (f)	50...60 Hz
Illuminance	5...2000 lx
Materiał	Material quality: Thermoplastic Material: Plastic
Rodzaj montażu	Flush Mounted
Number of Outputs	1
Typ produktu	Busch-Presence detector Universal, e-contact
Nazwa produktu	Busch-Presence detector Universal, e-contact 12 meters
Product Range	Movement detector
Napięcie znamionowe (U_r)	230 V
Data RoHS	20150724
Surface Finishing	Surface protection: Lacquered Surface finishing: Matt

Certyfikaty i deklaracje (Numer dokumentu)

Arkusze danych, informacja techniczna	2CKA001473B9577
Deklaracja zgodności - CE	2CKA100000E0708
Dane RoHS	9AKK104295D8727

Klasyfikacje	
ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → StandAlone Electronics → Presence Detector → Presence Detector Series → IR Controlled Devices (Master) → Presence Detector Universal, e Contact

