

PRODUCT-DETAILS

6819/51-183-500

6819/51-183-500 Busch-Presence detector Corridor BT, relay 30 metres



Ogólne informacje

Extended Product Type	6819/51-183-500
ID Produktu	2CKA006800A2779
Numer EAN	4011395218044
Opis katalogowy	6819/51-183-500 Busch-Presence detector Corridor BT, relay 30 metres

Opis	Master presence detector with mixed light measurement. For switching lighting systems that depend on brightness and movement. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. With power relays for LED operation. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 30 m x 3 m, frontal 20 m x 3 m. Extension of the detection range by means of master/slave combination. Mounting height 27 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor). With brightness-independent test mode for evaluating the detection zone. With detection display in test mode. Ceiling installation using integrated spring bracket. Twist protection via additional quick tensioning. Adjustment elements accessible on the front side. Surveillance density: 92 sectors with 368 switching segments Individual deactivation and adjustment of sensitivity of individual sensors possible. Switch-off delay: approx. 1 min. - 30 min. or short-time pulse adjustable. With selectable dynamic switch-off delay. Suitable for false ceilings with a board thickness from 9 to 25 mm.
------	--

Charakterystyka zamówienia

Numer EAN	4011395218044
-----------	---------------

Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85365080

Wymiary

Szerokość produktu netto	0.094 m
Wysokość produktu netto	0.094 m
Głębokość produktu netto	0.076 m
Waga produktu netto	0.17 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.141 m
Wysokość opakowania (poziom 1)	0.095 m
Długość opakowania (poziom 1)	0.165 m
Waga opakowania brutto (poziom 1)	316 g
EAN opakowania (poziom 1)	4011395218044

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Dodatkowe informacje

Napięcie pomocnicze AC/DC	110 V AC/DC 230 V AC/DC
Brand / Label	ABB
Kolor	aluminium silver
Rodzaj podłączenia	Plug Clamp
Zakres prądowy	Maximum 800 A
Stopień ochrony obudowy	IP40
Częstotliwość (f)	50...60 Hz
Illuminance	5...2000 lx
Materiał	Material quality: Thermoplastic Material: Plastic
Rodzaj montażu	Flush Mounted
Number of Outputs	1
Typ produktu	Busch-Presence detector Corridor BT, relay
Nazwa produktu	Busch-Presence detector Corridor BT, relay 30 metres
Product Range	Movement detector
Napięcie znamionowe (U _r)	230 V

Data RoHS

20150724

Surface Finishing

Surface protection: Lacquered

Surface finishing: Matt

Certyfikaty i deklaracje (Numer dokumentu)

Arkusz danych, informacja
techniczna

2CKA001473B9577

Deklaracja zgodności - CE

2CKA200000E6522

Dane RoHS

9AKK104295D8727

Klasyfikacje

ETIM 5

EC000133 - Movement sensor complete

ETIM 6

EC000133 - Movement sensor complete

ETIM 7

EC000133 - Movement sensor complete

WEEE Category

5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → StandAlone Electronics → Presence Detector → Presence Detector Series → Bluetooth
Controlled Devices (Master) → Presence Detector Corridor BT, Relay

