

PRODUCT-DETAILS

6819/55-183-500

6819/55-183-500 Busch-Presence detector Corridor BT, DALI 30 metres



Ogólne informacje

Extended Product Type	6819/55-183-500
ID Produktu	2CKA006800A2783
Numer EAN	4011395218136
Opis katalogowy	6819/55-183-500 Busch-Presence detector Corridor BT, DALI 30 metres

Opis

Master presence detector with mixed light measurement. For regulating and switching of DALI operating devices that depend on brightness and movement. For DALI broadcast operation (central telegram). Supplies the required voltage for additional DALI operating units and controllers. Suitable for up to 45 DALI operating devices. For changing the colour temperature of >tunable white< lamps, which meet DALI Standard IEC 62386-209 (Device Type 8). Colour temperature can then be set between 2,700 K - 6,500 K. With additional switching output for the activation of heating, air conditioning and ventilation or for switching additional loads (e.g. panel light). Configuration possible up to the complete deactivation of the DALI operating devices. With Bluetooth interface for parameterization and operation. Adjustment of all setting options via smartphone or tablet. Light control via smartphone or tablet app. Detection range (for installation height of 3 m): rectangular Walking persons: crosswise to the detector 30 m x 3 m, frontal 20 m x 3 m. Extension of the detection range by means of master/slave combination. Mounting height 27 mm. For semi-automatic, comfort and fully automatic operation. Additional activation/deactivation possibility through pushbutton input. With continuous light/continuous off function (8 hours), activation via intelligent extension unit input possible. With time-controlled basic illumination function. With selectable warm-up function for fluorescent lamps. With 2-step automatic switch-off (according to EnEV / EN 15232). With time-controlled night anti-glare function. With selectable presence simulation in case of non-presence. With integrated storage of ON period (energy monitor).

Charakterystyka zamówienia

Numer EAN	4011395218136
Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85365080

Wymiary

Szerokość produktu netto	0.094 m
Wysokość produktu netto	0.094 m
Głębokość produktu netto	0.087 m
Waga produktu netto	0.163 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.141 m
Wysokość opakowania (poziom 1)	0.095 m
Długość opakowania (poziom 1)	0.165 m
Waga opakowania brutto (poziom 1)	337 g
EAN opakowania (poziom 1)	4011395218136

Normy środowiskowe

Status RoHS	Zgodny z dyrektywą EU 2002/95/EC sierpień 18, 2005 i poprawkami
-------------	---

Dodatkowe informacje

Napięcie pomocnicze AC/DC	110 V AC/DC 230 V AC/DC
Brand / Label	ABB
Kolor	aluminium silver
Rodzaj podłączenia	Plug Clamp
Zakres prądowy	Maximum 800 A
Stopień ochrony obudowy	IP40
Częstotliwość (f)	50...60 Hz
Illuminance	5...2000 lx
Materiał	Material quality: Thermoplastic Material: Plastic
Rodzaj montażu	Flush Mounted
Number of Outputs	1
Typ produktu	Busch-Presence detector Corridor BT, DALI
Nazwa produktu	Busch-Presence detector Corridor BT, DALI 30 metres
Product Range	Movement detector

Napięcie znamionowe (U_r)	230 V
Data RoHS	20150727
Surface Finishing	Surface protection: Lacquered Surface finishing: Matt

Certyfikaty i deklaracje (Numer dokumentu)

Arkusz danych, informacja techniczna	2CKA001473B9577
Deklaracja zgodności - CE	2CKA200000E6526
Dane RoHS	9AKK104295D8727

Klasyfikacje

ETIM 5	EC000133 - Movement sensor complete
ETIM 6	EC000133 - Movement sensor complete
ETIM 7	EC000133 - Movement sensor complete
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → StandAlone Electronics → Presence Detector → Presence Detector Series → Bluetooth Controlled Devices (Master) → Presence Detector Corridor BT, DALI

