

PRODUCT-DETAILS

N2155.9 AN

N2155.9 AN - USB female-female connection unit - 1M - Anthracite



General Information

Extended Product Type	N2155.9 AN
Product ID	2CLA215590N1801
EAN	8427238142425
Catalog Description	N2155.9 AN - USB female-female connection unit - 1M - Anthracite
Long Description	Color: Anthracite. Front: 1x USB 2.0 connector (Type A connector) Rear: 1x USB 2.0 connector (Type A connector) fitted at 90° angle Size: 1 module.

Ordering

EAN	8427238142425
Minimum Order Quantity	1 piece
Customs Tariff Number	85369010

Dimensions

Product Net Width	22 mm
Product Net Height	44 mm
Product Net Weight	0.053 kg

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.033 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.053 kg
Package Level 1 EAN	8427238142425

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
-------------------------	--

Additional Information

Color	Anthracite
Degree of Protection	IP20
Material	Material quality: Thermoplastic Material: Plastic
Mounting Type	Flush mounted (plaster)
Product Main Type	Zenit
Product Name	USB female-female connection unit - 1M - Anthracite
Surface Finishing	Surface protection: Decor Surface finishing: Matt

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK10103A5108
Declaration of Conformity - CE	9AKK106930A1758
Instructions and Manuals	2CLX215509N1001

Classifications

ETIM 5	EC000018 - Insert/cover for communication technology
ETIM 6	EC000018 - Insert/cover for communication technology
ETIM 7	EC000018 - Insert/cover for communication technology
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Modular Range - Niessen → Design Zenit → Flush Mounted Inserts with Cover Plate → VDI Connector

Low Voltage Products and Systems → Switch Assortments → VDI - Voice / Data / Image Connectors → VDI Connector → VDI Connector - Flush Mounted → VDI Connector

