

PRODUCT-DETAILS

N2260.3 BL

N2260.3 BL - LED rotatory/push dimmer - 2M - White



Ogólne informacje

Extended Product Type	N2260.3 BL
ID Produktu	2CLA226030N1101
Numer EAN	8427238138329
Opis katalogowy	N2260.3 BL - LED rotatory/push dimmer - 2M - White

Opis	Color: White.
	Rated voltage: 230 Vac $\pm$ 10%
	Frequency: 50 Hz (Nominal power: 250 W/VA) / 60 Hz (Nominal power: 200 W/VA)
	Power (min./max load):
	- LEDi: 2 / 100 W/VA (max. 10 lamps)
	- Dimmable energy saving lamps: 2 / 100 W/VA (max. 10 lamps)
	- LV LEDi with transformer (only type L or LC): 4 / 100 W/VA (max. 10 lamps)
	- Incandescent lamps: 10 / 250 W/VA
	- Halogen lamps: 10 / 250 W/VA
	- LV halogen with transformer (only type L or LC): 10 / 250 W/VA (max. 10 lamps)
2 wire connection	
Optional: auxiliary on/off with 2-way switch N2X02	
Indicator LED lamp included	
Back-up fuse: Electronic	
Overload protection: Electronic	
Ambient temperature: 0°C to +35°C	
Size: 2 modules.	

Charakterystyka zamówienia

Numer EAN	8427238138329
-----------	---------------

Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85365080

Wymiary

Szerokość produktu netto	44 mm
Wysokość produktu netto	44 mm
Waga produktu netto	0.08 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.076 m
Wysokość opakowania (poziom 1)	0.064 m
Długość opakowania (poziom 1)	0.076 m
Waga opakowania brutto (poziom 1)	0.08 kg
EAN opakowania (poziom 1)	8427238138329

Normy środowiskowe

Temperatura powietrza otoczenia	Eksplatacja -5 ... +35 °C Przechowywanie -5 ... +50 °C
---------------------------------	---

Dodatkowe informacje

Typ napędu	Turn button
Kolor	White
Rodzaj podłączenia	Screw
Stopień ochrony obudowy	IP20
Częstotliwość (f)	50...60 Hz
Rodzaj obciążenia	Universal and LED Retrofit
Materiał	Material quality: Thermoplastic Material: Plastic
Rodzaj montażu	Flush mounted (plaster)
Typ produktu	Zenit
Nazwa produktu	LED rotatory/push dimmer - 2M - White
Napięcie znamionowe (U _r)	230...230 V
ID produktu zastąpionego	2CL0N226031
Surface Finishing	Surface protection: Untreated Surface finishing: Glossy

Certyfikaty i deklaracje (Numer dokumentu)

Arkusz danych, informacja techniczna	9AKK10103A5108
Deklaracja zgodności - CE	9AKK106930A5901
Instrukcje i podręczniki	2CLX226039N1001

Klasyfikacje

ETIM 5	EC000025 - Dimmer
ETIM 6	EC000025 - Dimmer
ETIM 7	EC000025 - Dimmer
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted Modular Range - Niessen → Design Zenit → Flush Mounted Inserts with Cover Plate → Dimmers

Produkty niskiego napięcia i systemy → Switch Assortments → Light / LoadControl → Electronic Rotary / Push Button Dimmer (all Loads incl. LED, DALI) → Push Button Dimmer - Flush Mounted → Dimmers

