

PRODUCT-DETAILS

## N2281 BL

## N2281 BL - Beacon LED light - 2M - White



General Information	
Extended Product Type	N2281 BL
Product ID	2CLA228100N1101
EAN	8427238063164
Catalog Description	N2281 BL - Beacon LED light - 2M - White
Long Description	Rated voltage: 230 Vac / 50 Hz Lamp: blue and high luminosity white LED (selectable with rotatory switch) Luminous flux: > 2 lumen at 1 meter White diffuser Autonomy: 3 hours (1 hour at maximum illumination 2 hours with lower illumination) Battery: Ni-MH (estimated lifetime: 4 years). Size: 2 modules.

Ordering	
EAN	8427238063164
Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions	
Product Net Width	44 mm
Product Net Height	44 mm
Product Net Length	44 mm
Product Net Weight	0.072 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.052 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.072 kg
Package Level 1 EAN	8427238063164

## Environmental Ambient Air Temperature Operation -5 ... +35 °C Storage -5 ... +50 °C

Additional Information	
Connection Type	Screw
Degree of Protection	IP20
Function	Escape route lighting/signage
Housing Material	Plastic
Illuminance	2 lm
Input Voltage Type	AC
Lamp Type	LED not exchangeable
Mounting Type	Built-in
Number of Poles	2
Operate Time	13 hour
	7 W
Product Main Type	Zenit
Product Name	Beacon LED light - 2M - White
Protection Class	Isolated
Rated Voltage (U <sub>r</sub> )	230230 V
Replaced Product ID (OLD)	2CL0N228101

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	9AKK10103A5108
Declaration of Conformity - CE	9AKK106930A5902
Instructions and Manuals	2CLX818139A1001

Classifications	
ETIM 5	EC000399 - Indication- and signalling lamp
ETIM 6	EC001957 - Emergency luminaire
ETIM 7	EC001957 - Emergency luminaire
UNSPSC	39121534
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

N2281 BL 3

## **Categories**

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ Modular\ Range\ -\ Niessen \rightarrow Design\ Zenit \rightarrow Flush\ Mounted\ Inserts\ with\ Cover\ Plate \rightarrow LED\ Light\ /\ Light\ Signal$ 

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow LED\ Light\ /\ Light\ Signals \rightarrow LED\ Light\ /\ Light\ Signal \rightarrow LED\ Light\ /\ Light\ Signal\ Dight\ /\ Light\ Signal\ Dight\ Dight\$ 

