

PRODUCT-DETAILS

N2328 BL

N2328 BL - American earthed duplex socket outlet - 3M - White



General Information

Extended Product Type	N2328 BL
Product ID	2CLA232800N1101
EAN	8427238085654
Catalog Description	N2328 BL - American earthed duplex socket outlet - 3M - White
Long Description	Color: White. Rated voltage: 125 Vac Rated current: 15A Type B: 2P + E / NEMA 5-15R Duplex outlet Shuttered for child safety Screw terminals Size: 3 modules.

Ordering

EAN	8427238085654
Minimum Order Quantity	20 piece
Customs Tariff Number	85366990

Dimensions

Product Net Width	66 mm
Product Net Height	44 mm
Product Net Weight	0.05 kg

Container Information

Package Level 1 Units	box 20 piece
Package Level 1 Width	0.145 m
Package Level 1 Height	0.089 m
Package Level 1 Depth / Length	0.237 m
Package Level 1 Gross Weight	1 kg
Package Level 1 EAN	8427238085654

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
-------------------------	--

Additional Information

Color	White
Connection Type	Screw
Degree of Protection	IP20
Frequency (f)	50...60 Hz
Material	Plastic
Mounting Type	Flush mounted (plaster)
Number of Phases	2
Product Main Type	Zenit
Product Name	American earthed duplex socket outlet - 3M - White
Rated Current (I _n)	15 A
Rated Voltage (U _r)	250 V
Replaced Product ID (OLD)	2CL0N232801
Surface Finishing	Surface protection: Untreated Surface finishing: Glossy

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK10103A5108
Instructions and Manuals	2CLX210109N1001

Classifications

ETIM 5	EC000125 - Socket outlet
ETIM 6	EC000125 - Socket outlet
ETIM 7	EC000125 - Socket outlet
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted Modular Range - Niessen → Design Zenit → Flush Mounted Inserts with Cover Plate → Single Socket Outlets

Low Voltage Products and Systems → Switch Assortments → Socket Outlets → Single Socket Outlets → Single Socket Outlets - Flush Mounted → Single Socket Outlets

