

PRODUCT-DETAILS

8130.2

8130.2 - Universal double relay time delayed switch



General Information

Extended Product Type	8130.2
Product ID	2CLA813020A1001
EAN	8427238057309
Catalog Description	8130.2 - Universal double relay time delayed switch
Long Description	Rated voltage: 230 V~, +10 % / -10 % Rated frequency: 50 Hz For switching incandescent lamps, 230 V tungsten halogen lamps, fluorescent lamps and low-voltage halogen lamps, that are actuated via transformers. 3 wire connection (neutral conductor required). With operating mode switch for operating mode: switch, time switch. Switch operating mode: press on the upper rocker switch half to switch the light on, press on the lower rocker switch half to switch the light off. Time switch operating mode: press on the upper rocker switch half to switch the light on, the light automatically switches off after a time delay. Manual switching off not possible. The delay can be set in 5 steps between 30 and 300 secs. Operation also possible via conventional push buttons 8104.X. Inputs: 1 Polling voltage: 230 V~, Sensing pulse, L-wire Outputs: 2 Normally open contacts, potential-bound Suitable for: ohmic, capacitive and inductive loads Rated current: 2x 3 AX Rated power: 2x 700 W/VA Included: attachable claws. Electronic cover plate code: 8530, 8430, 8230 & 5530

Ordering

EAN	8427238057309
-----	---------------

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080

Dimensions

Product Net Width	0.073 m
Product Net Height	0.052 m
Product Net Depth / Length	0.073 m
Product Net Weight	0.102 kg

Container Information

Package Level 1 Units	1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.052 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.102 kg
Package Level 1 EAN	8427238057309

Environmental

Ambient Air Temperature	Operation -5 ... +35 °C Storage -5 ... +50 °C
-------------------------	--

Additional Information

Mounting Type	Flush mounted (plaster)
Number of Channels	4
Product Main Type	Wireless
Product Name	Universal double relay time delayed switch
Replaced Product ID (OLD)	2CL0813020

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	9AKK107046A0356
Declaration of Conformity - CE	9AKK106713A1745

Classifications

ETIM 5	EC001590 - Switch
ETIM 6	EC000257 - Transmitter/Remote control for domestic switching devices
ETIM 7	EC000257 - Transmitter/Remote control for domestic switching devices
UNSPSC	39122226
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Arco → Flush Mounted Inserts → Electronic Timer Inserts

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Olas → Flush Mounted Inserts → Electronic Timer Inserts

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → Electronic Timer Inserts

Low Voltage Products and Systems → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Tacto → Flush Mounted Inserts → Electronic Timer Inserts

Low Voltage Products and Systems → Switch Assortments → Light / LoadControl → Electronic Timer → Electronic Timer - Flush Mounted → Electronic Timer Inserts

