

PRODUCT-DETAILS

8130.2

8130.2 - Universal double relay time delayed switch



Ogólne informacje

Extended Product Type	8130.2
ID Produktu	2CLA813020A1001
Numer EAN	8427238057309
Opis katalogowy	8130.2 - Universal double relay time delayed switch
Opis	Rated voltage: 230 V~, +10 % / -10 %
	Rated frequency: 50 Hz
	For switching incandescent lamps, 230 V tungsten halogen lamps, fluorescent lamps and low-voltage halogen lamps, that are actuated via transformers.
	3 wire connection (neutral conductor required).
	With operating mode switch for operating mode: switch, time switch.
	Switch operating mode: press on the upper rocker switch half to switch the light on, press on the lower rocker switch half to switch the light off.
	Time switch operating mode: press on the upper rocker switch half to switch the light on, the light automatically switches off after a time delay. Manual switching off not possible. The delay can be set in 5 steps between 30 and 300 secs.
	Operation also possible via conventional push buttons 8104.X.
	Inputs: 1
	Polling voltage: 230 V~, Sensing pulse, L-wire
Outputs: 2 Normally open contacts, potential-bound	
Suitable for: ohmic, capacitive and inductive loads	
Rated current: 2x 3 AX	
Rated power: 2x 700 W/VA	
Included: attachable claws.	
Electronic cover plate code: 8530, 8430, 8230 & 5530	

Charakterystyka zamówienia

Numer EAN	8427238057309
Minimalna ilość zamówienia	1 sztuka
Kod taryfy celnej	85365080

Wymiary

Szerokość produktu netto	0.073 m
Wysokość produktu netto	0.052 m
Głębokość produktu netto	0.073 m
Waga produktu netto	0.102 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.073 m
Wysokość opakowania (poziom 1)	0.052 m
Długość opakowania (poziom 1)	0.073 m
Waga opakowania brutto (poziom 1)	0.102 kg
EAN opakowania (poziom 1)	8427238057309

Normy środowiskowe

Temperatura powietrza otoczenia	Eksploatacja -5 ... +35 °C Przechowywanie -5 ... +50 °C
---------------------------------	--

Dodatkowe informacje

Rodzaj montażu	Flush mounted (plaster)
Number of Channels	4
Typ produktu	Wireless
Nazwa produktu	Universal double relay time delayed switch
ID produktu zastąpionego	2CL0813020

Certyfikaty i deklaracje (Numer dokumentu)

Arkusze danych, informacja techniczna	9AKK107046A0356
Deklaracja zgodności - CE	9AKK106713A1745

Klasyfikacje

ETIM 5	EC001590 - Switch
--------	-------------------

ETIM 6	EC000257 - Transmitter/Remote control for domestic switching devices
ETIM 7	EC000257 - Transmitter/Remote control for domestic switching devices
UNSPSC	39122226
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Arco → Flush Mounted Inserts → Electronic Timer Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Olas → Flush Mounted Inserts → Electronic Timer Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → Electronic Timer Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Tacto → Flush Mounted Inserts → Electronic Timer Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Light / LoadControl → Electronic Timer → Electronic Timer - Flush Mounted → Electronic Timer Inserts

